

## Safety Data Sheet

according to UK REACH Regulation

### Bouin Allen Fixative

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 1 of 18

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Bouin Allen Fixative

UFI: RF71-31PH-G008-7CT3

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Uses advised against

Any non-intended use.

### 1.3. Details of the supplier of the safety data sheet

Company name: MORPHISTO GmbH  
Street: Schumannstr. 142/144  
Place: D-63069 Offenbach  
Telephone: +49 (0) 69 / 400 3019-60      Telefax: +49 (0) 69 / 400 3019-64  
E-mail: info@morphisto.de  
Contact person: Morphisto GmbH  
E-mail: gefahrstoffmanagement@morphisto.de  
Internet: http://www.morphisto.de

### 1.4. Emergency telephone number:

Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### GB CLP Regulation

Acute Tox. 4; H302  
Acute Tox. 4; H332  
Skin Corr. 1; H314  
Eye Dam. 1; H318  
Resp. Sens. 1; H334  
Skin Sens. 1; H317  
Muta. 1B; H340  
Carc. 1A; H350  
STOT SE 3; H335  
STOT RE 2; H373  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture was classified as corrosive precautionary due to an extreme pH-value.

### 2.2. Label elements

#### GB CLP Regulation

#### Hazard components for labelling

formaldehyde%  
Acetic acid%  
methanol  
chromium (VI) trioxide

Signal word: Danger

#### Pictograms:



## Safety Data Sheet

according to UK REACH Regulation

### Bouin Allen Fixative

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 2 of 18

#### Hazard statements

H302+H332	Harmful if swallowed or if inhaled.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P201	Obtain special instructions before use.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

#### Special labelling of certain mixtures

Restricted to professional users.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

#### Pictograms:



#### Hazard statements

H314-H317-H334-H340-H350-H412

#### Precautionary statements

P201-P260-P280-P303+P361+P353-P304+P340-P305+P351+P338-P310

#### 2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

**Safety Data Sheet**

according to UK REACH Regulation

**Bouin Allen Fixative**

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 3 of 18

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
50-00-0	formaldehyde%			5 - < 10 %
	200-001-8	605-001-00-5	01-2119488953-20	
	Carc. 1B, Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Skin Sens. 1; H350 H341 H331 H311 H301 H314 H317			
64-19-7	Acetic acid%			5 - < 10 %
	200-580-7	607-002-00-6	01-2119475328-30	
	Flam. Liq. 3, Skin Corr. 1A; H226 H314			
67-56-1	methanol			1 - < 5 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			
1333-82-0	chromium (VI) trioxide			1 - < 5 %
	215-607-8	024-001-00-0	01-2119458868-17	
	Ox. Sol. 1, Carc. 1A, Muta. 1B, Repr. 2, Acute Tox. 2, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1A, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H271 H350 H340 H361f H330 H311 H301 H314 H318 H334 H317 H335 H372 H400 H410			
88-89-1	picric acid			< 1 %
	201-865-9	609-009-00-X		
	Expl. 1.1, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3; H201 H331 H311 H301			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
50-00-0	200-001-8	formaldehyde%	5 - < 10 %
		inhalation: LC50 = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: LD50 = 292 mg/kg; oral: LD50 = 100 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 5 - < 25 Eye Irrit. 2; H319: >= 5 - < 25 Skin Sens. 1; H317: >= 0,2 - 100 STOT SE 3; H335: >= 5 - 100	
64-19-7	200-580-7	Acetic acid%	5 - < 10 %
		inhalation: LC50 = >40 mg/l (vapours); oral: LD50 = 3530 mg/kg Skin Corr. 1A; H314: >= 90 - 100 Skin Corr. 1B; H314: >= 25 - < 90 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25	
67-56-1	200-659-6	methanol	1 - < 5 %
		inhalation: LC50 = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: LD50 = 300 mg/kg; oral: LD50 = 100 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10	
1333-82-0	215-607-8	chromium (VI) trioxide	1 - < 5 %
		inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = 57 mg/kg; oral: LD50 = 52 mg/kg STOT SE 3; H335: >= 1 - 100 Aquatic Acute 1; H400: M=10	
88-89-1	201-865-9	picric acid	< 1 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: LC50 = 0,51 mg/l (dusts or mists); dermal: LD50 = 300,1 mg/kg; oral: LD50 = 200 mg/kg	

**Further Information**

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: chromium (VI) trioxide (CAS: 1333-82-0)

**Safety Data Sheet**

according to UK REACH Regulation

**Bouin Allen Fixative**

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 4 of 18

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove affected person from the danger area and lay down. To supervise the blood circulation. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove contaminated, saturated clothing immediately. First aider: Pay attention to self-protection! Use appropriate respiratory protection.

**After inhalation**

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. In case of irregular breathing or respiratory arrest provide artificial respiration. No direct artificial respiration to be given by first aider. Call a physician immediately.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.

**After ingestion**

Observe risk of aspiration if vomiting occurs. Adverse human health effects and symptoms: Gastric perforation. Do not allow a neutralisation agent to be drunk. Rinse mouth thoroughly with water. Let water be drunk in little sips (dilution effect). Do NOT induce vomiting. Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

**4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings. alcohol resistant foam. dry extinguishing powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Non-flammable. Explosive when dry. In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Formaldehyde. Nitrogen oxides (NO<sub>x</sub>).

**5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. In case of fire and/or explosion do not breathe fumes.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

**Safety Data Sheet**

according to UK REACH Regulation

**Bouin Allen Fixative**

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 5 of 18

**General advice**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Ventilate affected area.  
Do not allow to dry. Risk of explosion in case of drying up. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

**For non-emergency personnel**

Ventilate affected area. Clear danger zone. Follow emergency plan. Consult an expert.

**For emergency responders**

Do not allow to dry. Risk of explosion in case of drying up. Stop leak if safe to do so. Move undamaged containers from immediate hazard area if it can be done safely.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Discharge into the environment must be avoided. Inform competent authorities in case of accidental release. (Larger quantities)

**6.3. Methods and material for containment and cleaning up****For containment**

Cover drains. Collect, embank and pump out. Observe possible material restrictions (section 10). Do not dry up the product.

**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. The contaminated area should be cleaned up immediately with: a concentrated aqueous sodium bisulfite solution. Rinse with water.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Technical ventilation of workplace. Use extractor hood (laboratory). Wear suitable protective clothing. ( See section 8. ) Avoid exposure - obtain special instructions before use.  
Avoid contact with skin, eyes and clothes. Always close containers tightly after the removal of product.

**Advice on protection against fire and explosion**

Usual measures for fire prevention. Do not allow to dry. Risk of explosion in case of drying up.

**Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product. Wash contaminated clothing prior to re-use. Used working clothes should not be worn outside the work area. Street clothing should be stored separately from work clothing.

**Further information on handling**

Always remove adhering product residues from lids and closures before closing the product.  
General protection and hygiene measures: refer to section 8

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep/Store only in original container. Make sure spills can be contained, e.g. in sump pallets or kerbed areas. Storage: Just as long as necessary.  
Unsuitable materials for Container: metal.

## Safety Data Sheet

according to UK REACH Regulation

### Bouin Allen Fixative

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 6 of 18

#### Hints on joint storage

Do not store together with: food and feed. pharmaceuticals. Infectious substances. Radioactive substances. Explosive substances. Oxidizing substances. Oxidizing liquids. Organic peroxides. Self-reactive substances and mixtures. Pyrophoric solids. Substances which in contact with water form flammable gases. Ammonium nitrate and preparations containing ammonium nitrate. Gas.. Oxidizing liquids. Oxidizing solids. Combustible toxic substances. Non-combustible toxic substances.

#### Further information on storage conditions

Ensure adequate ventilation of the storage area. Store small packages in a suitable, robust cabinet. Protect against: UV-radiation/sunlight., Heat Recommended storage temperature: 15-25°. Do not allow to dry. Risk of explosion in case of drying up.

#### 7.3. Specific end use(s)

See section 1.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
64-19-7	Acetic acid	10	25		TWA (8 h)	WEL
		20	50		STEL (15 min)	WEL
-	Chromium (VI) compounds (as Cr)	-	0.01		TWA (8 h)	WEL
50-00-0	Formaldehyde	2	2.5		TWA (8 h)	WEL
		2	2.5		STEL (15 min)	WEL
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL
88-89-1	Picric acid	-	0.1		TWA (8 h)	WEL
		-	0.3		STEL (15 min)	WEL

##### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
-	Chromium VI	chromium (creatinine)	10 µmol/mol	urine	Post shift

**Safety Data Sheet**

according to UK REACH Regulation

**Bouin Allen Fixative**

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 7 of 18

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
50-00-0	formaldehyde%			
Worker DNEL, acute		inhalation	systemic	1 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	240 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	0,5 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	0,375 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	0,75 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	local	0,037 mg/cm <sup>2</sup>
64-19-7	Acetic acid%			
Worker DNEL, long-term		inhalation	local	25 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	25 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	25 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	25 mg/m <sup>3</sup>
67-56-1	methanol			
Worker DNEL, acute		inhalation	local	260 mg/m <sup>3</sup>
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	260 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	260 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	40 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	260 mg/m <sup>3</sup>

**Safety Data Sheet**

according to UK REACH Regulation

**Bouin Allen Fixative**

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 8 of 18

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
50-00-0	formaldehyde%	
Freshwater		0,44 mg/l
Freshwater (intermittent releases)		4,44 mg/l
Marine water		0,44 mg/l
Freshwater sediment		2,3 mg/kg
Marine sediment		2,3 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,19 mg/l
Soil		0,2 mg/kg
64-19-7	Acetic acid%	
Freshwater		3,058 mg/l
Freshwater (intermittent releases)		30,58 mg/l
Marine water		0,306 mg/l
Freshwater sediment		11,36 mg/kg
Marine sediment		1,136 mg/kg
Micro-organisms in sewage treatment plants (STP)		85 mg/l
Soil		0,47 mg/kg
67-56-1	methanol	
Freshwater		20,8 mg/l
Marine water		2,08 mg/l
Marine water (intermittent releases)		1540 mg/l
Freshwater sediment		77 mg/kg
Marine sediment		7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		3,18 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Technical measures and the application of suitable work processes have priority over personal protection equipment. Technical ventilation of workplace. Process within closed systems. Use extractor hood (laboratory). Provide washing facilities at the workplace, provide an eye shower or eyewash bottle and mark them.

**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

Suitable eye protection: goggles. Tightly sealed safety glasses. Eye glasses with side protection EN 166

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the



## Safety Data Sheet

according to UK REACH Regulation

### Bouin Allen Fixative

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 9 of 18

supplier of these gloves. Pull-over gloves of rubber. EN ISO 374 Suitable material:

(penetration time (maximum wearing period):  $\geq$  8 Stunden):

Butyl rubber.

(penetration time (maximum wearing period):  $\geq$  4 Stunden):

FKM (fluororubber).

(penetration time (maximum wearing period):  $\geq$  1 Stunde):

CR (polychloroprenes, Chloroprene rubber).

Before using check leak tightness / impermeability.

#### Skin protection

Use of protective clothing. Chemical protection clothing, Lab apron.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection necessary at:

Insufficient ventilation., insufficient absorption., exceeding exposure limit values, Release of: product.

Suitable respiratory protective equipment: Self-contained respirator (breathing apparatus)

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. The wearing time limitations according to GefStoffV in conjunction with the rules for the use of respiratory protective devices (BGR 190) must be observed.

#### Thermal hazards

Do not dry up the product. Risk of explosion in case of drying up.

#### Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	yellow transparent	
Odour:	characteristic	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		97 °C
Flammability:		not determined
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		not determined
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value (at 20 °C):		1-2
Viscosity / kinematic:		not determined
Water solubility: (at 20 °C)		completely miscible
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure: (at 20 °C)		23 hPa
Density (at 20 °C):		1,04 g/cm <sup>3</sup>
Relative vapour density:		not determined
Particle characteristics:		not applicable

### 9.2. Other information

## Safety Data Sheet

according to UK REACH Regulation

### Bouin Allen Fixative

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 10 of 18

#### Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive. Do not dry up the product. Risk of explosion in case of drying up.

Sustaining combustion:

Not sustaining combustion

Oxidizing properties

none

#### Other safety characteristics

Evaporation rate:

not determined

Pour point:

not determined

Viscosity / dynamic:

not determined

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Possibility of hazardous reactions.

### 10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

Exothermic reaction with: Base, Peroxides, Oxidizing agent. Reaction with: peroxides, for example hydrogen peroxide. Chrom(VI)-oxide. permanganates, e.g. potassium permanganate. Performic acid, perchloric acid. Phosphorus trichloride. Alcohols. Nitric acid. Ammonium nitrate. Aniline.

### 10.4. Conditions to avoid

Keep away from heat. Do not allow to dry. Risk of explosion in case of drying up. Protect from direct sunlight.

### 10.5. Incompatible materials

Keep away from: Base, Oxidizing agent, Peroxides. Information is given in subsection 10.3.

### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Formaldehyde. Nitrogen oxides (NO<sub>x</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Harmful if swallowed.

Harmful if inhaled.

#### ATEmix calculated

ATE (oral) 643,2 mg/kg; ATE (dermal) 2003 mg/kg; ATE (inhalation vapour) 13,75 mg/l; ATE (inhalation dust/mist) 1,820 mg/l

**Safety Data Sheet**

according to UK REACH Regulation

**Bouin Allen Fixative**

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 11 of 18

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
50-00-0	formaldehyde%				
	oral	LD50 100 mg/kg	Rat	GESTIS	
	dermal	LD50 292 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 3 mg/l	Rat	suppliers SDS.	
	inhalation dust/mist	ATE 0,5 mg/l			
64-19-7	Acetic acid%				
	oral	LD50 3530 mg/kg	Rat	GESTIS	
	inhalation (4 h) vapour	LC50 >40 mg/l	Rat	suppliers SDS.	
67-56-1	methanol				
	oral	LD50 100 mg/kg	Rat	suppliers SDS.	
	dermal	LD50 300 mg/kg	Rabbit	suppliers SDS.	
	inhalation (4 h) vapour	LC50 3 mg/l	Rat	suppliers SDS.	
	inhalation dust/mist	ATE 0,5 mg/l			
1333-82-0	chromium (VI) trioxide				
	oral	LD50 52 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 57 mg/kg	Rabbit	ECHA	OECD 402
	inhalation vapour	ATE 0,5 mg/l			
	inhalation dust/mist	ATE 0,05 mg/l			
88-89-1	picric acid				
	oral	LD50 200 mg/kg	Rat	RTECS	
	dermal	LD50 300,1 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation (4 h) dust/mist	LC50 0,51 mg/l			

**Irritation and corrosivity**

Causes severe skin burns and eye damage. (On basis of test data)

Causes serious eye damage. (On basis of test data)

**Sensitising effects**

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (chromium (VI) trioxide)

May cause an allergic skin reaction. (formaldehyde%; chromium (VI) trioxide)

**Carcinogenic/mutagenic/toxic effects for reproduction**

May cause genetic defects. (chromium (VI) trioxide)

May cause cancer. (formaldehyde%; chromium (VI) trioxide)

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (formaldehyde%; chromium (VI) trioxide)

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (chromium (VI) trioxide)

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Safety Data Sheet**

according to UK REACH Regulation

**Bouin Allen Fixative**

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 12 of 18

**11.2. Information on other hazards**
**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**Other information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

**SECTION 12: Ecological information**
**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
50-00-0	formaldehyde%					
	Acute fish toxicity	LC50 mg/l	24,1	96 h	Pimephales promelas	ECHA Dossier
	Acute algae toxicity	ErC50 mg/l	4,89	72 h	Desmodesmus subspicatus	ECHA Dossier
	Acute crustacea toxicity	EC50 mg/l	5,8 mg/l	48 h	Daphnia pulex (water flea)	ECHA Dossier
64-19-7	Acetic acid%					
	Acute fish toxicity	LC50 mg/l	>300	96 h	Oncorhynchus mykiss	ECHA Dossier
	Acute algae toxicity	ErC50 mg/l	>300	72 h	Skeletonema costatum	ECHA Dossier
	Acute crustacea toxicity	EC50 mg/l	>300	48 h	Daphnia magna	ECHA Dossier
67-56-1	methanol					
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	ECHA Dossier
	Acute algae toxicity	ErC50 mg/l	22000	96 h	Pseudokirchneriella subcapitata	ECHA Dossier
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna	ECHA Dossier OECD 202
1333-82-0	chromium (VI) trioxide					
	Acute fish toxicity	LC50 mg/l	33,2	96 h	Pimephales promelas	ECHA
	Acute crustacea toxicity	EC50 mg/l	0,035	48 h	Daphnia magna	ECHA

**12.2. Persistence and degradability**

The product has not been tested.

**Safety Data Sheet**

according to UK REACH Regulation

**Bouin Allen Fixative**

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 13 of 18

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
50-00-0	formaldehyde%			
	OECD Guideline 301 C	91 %	14	ECHA Dossier
	Easily biodegradable (concerning to the criteria of the OECD)			
	OECD Guideline 301 D	90	28	ECHA Dossier
	Product is biodegradable.			
64-19-7	Acetic acid%			
	Other guideline	95%	5	suppliers SDS.
	Easily biodegradable (concerning to the criteria of the OECD)			
67-56-1	methanol			
	other guideline	96%	20	ECHA Dossier
	Easily biodegradable (concerning to the criteria of the OECD)			

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
50-00-0	formaldehyde%	0,35
64-19-7	Acetic acid%	-0,17
67-56-1	methanol	-0,77

**BCF**

CAS No	Chemical name	BCF	Species	Source
64-19-7	Acetic acid%	3,16		
67-56-1	methanol	<10		

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Do not allow uncontrolled discharge of product into the environment.

**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**
**Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation. Hazardous waste according to Directive 2008/98/EC (waste framework directive). Consult the local waste disposal expert about waste disposal. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process. Do not dry up the product. Risk of explosion in case of drying up.

## Safety Data Sheet

according to UK REACH Regulation

### Bouin Allen Fixative

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 14 of 18

**List of Wastes Code - residues/unused products**

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

**List of Wastes Code - used product**

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

**List of Wastes Code - contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

**Contaminated packaging**

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled.

## SECTION 14: Transport information

**Land transport (ADR/RID)**

<b><u>14.1. UN number or ID number:</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.2. UN proper shipping name:</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.3. Transport hazard class(es):</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.4. Packing group:</u></b>	No dangerous good in sense of this transport regulation.

**Inland waterways transport (ADN)**

<b><u>14.1. UN number or ID number:</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.2. UN proper shipping name:</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.3. Transport hazard class(es):</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.4. Packing group:</u></b>	No dangerous good in sense of this transport regulation.

**Marine transport (IMDG)**

<b><u>14.1. UN number or ID number:</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.2. UN proper shipping name:</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.3. Transport hazard class(es):</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.4. Packing group:</u></b>	No dangerous good in sense of this transport regulation.

**Air transport (ICAO-TI/IATA-DGR)**

<b><u>14.1. UN number or ID number:</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.2. UN proper shipping name:</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.3. Transport hazard class(es):</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.4. Packing group:</u></b>	No dangerous good in sense of this transport regulation.

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

See section 8.

**14.7. Maritime transport in bulk according to IMO instruments**

not relevant

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**
**EU regulatory information**

## Safety Data Sheet

according to UK REACH Regulation

### Bouin Allen Fixative

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 15 of 18

Authorisations (REACH, annex XIV):  
chromium (VI) trioxide

Restrictions on use (REACH, annex XVII):  
Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III):  
Not subject to 2012/18/EU (SEVESO III)

#### Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

#### Additional information

The product is subject to the Chemicals Prohibition Ordinance (ChemVerbotsV). Observe the requirements and restrictions for handling and dispensing in Section 3 of the ChemVerbotsV, among others.

#### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

formaldehyde%

Acetic acid%

methanol

chromium (VI) trioxide

### SECTION 16: Other information

#### Changes

Rev. 1,0; 09.04.2024; Individual safety data sheet based on10153\_collect

**Safety Data Sheet**

according to UK REACH Regulation

**Bouin Allen Fixative**

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 16 of 18

**Abbreviations and acronyms**

Expl: Explosives  
Ox. Sol: Oxidising solids  
Flam. Liq: Flammable liquids  
Acute Tox: Acute toxicity  
Skin Corr: Skin corrosion  
Eye Dam: Eye damage  
Resp. Sens: Respiratory sensitisation  
Skin Sens: Skin sensitisation  
Muta: Germ cell mutagenicity  
Carc: Carcinogenicity  
Repr: Reproductive toxicity  
STOT SE: Specific target organ toxicity - single exposure  
STOT RE: Specific target organ toxicity - repeated exposure  
Aquatic Acute: Acute aquatic hazard  
Aquatic Chronic: Chronic aquatic hazard  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
CAS Chemical Abstracts Service  
DNEL: Derived No Effect Level  
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organization  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
LOAEL: Lowest observed adverse effect level  
LOAEC: Lowest observed adverse effect concentration  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
NOAEL: No observed adverse effect level  
NOAEC: No observed adverse effect level  
NTP: National Toxicology Program  
N/A: not applicable  
OSHA: Occupational Safety and Health Administration  
PNEC: predicted no effect concentration  
PBT: Persistent bioaccumulative toxic  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail )  
SARA: Superfund Amendments and Reauthorization Act  
SVHC: substance of very high concern  
TRGS Technische Regeln fuerGefahrstoffe  
TSCA: Toxic Substances Control Act  
VOC: Volatile Organic Compounds  
VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe  
WGK: Wassergefaehrdungsklasse  
CLP: Classification, labelling and Packaging  
REACH: Registration, Evaluation and Authorization of Chemicals  
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
UN: United Nations  
CAS: Chemical Abstracts Service  
DNEL: Derived No Effect Level  
DMEL: Derived Minimal Effect Level  
PNEC: Predicted No Effect Concentration



**Safety Data Sheet**

according to UK REACH Regulation

**Bouin Allen Fixative**

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 17 of 18

ATE: Acute toxicity estimate  
 LL50: Lethal loading, 50%  
 EL50: Effect loading, 50%  
 EC50: Effective Concentration 50%  
 ErC50: Effective Concentration 50%, growth rate  
 NOEC: No Observed Effect Concentration  
 BCF: Bio-concentration factor  
 PBT: persistent, bioaccumulative, toxic  
 vPvB: very persistent, very bioaccumulative  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 RID: Regulations concerning the international carriage of dangerous goods by rail  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation  
 intérieures)  
 EmS: Emergency Schedules  
 MFAG: Medical First Aid Guide  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 IBC: Intermediate Bulk Container  
 For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>  
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety  
 assessment, chapter R.20 (Table of terms and abbreviations).  
 EC/EEC: European Community/European Economic Community  
 EU: European Union  
 M-factor: Multiplying factor  
 IATA: International Air Transport Association  
 DGR: Dangerous Goods Regulations  
 ICAO: International Civil Aviation Organization  
 TI: Technical Instructions  
 VOC: volatile organic compound

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Corr. 1; H314	On basis of test data
Eye Dam. 1; H318	On basis of test data
Resp. Sens. 1; H334	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 1B; H340	Calculation method
Carc. 1A; H350	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H201 Explosive; mass explosion hazard.  
 H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H271 May cause fire or explosion; strong oxidiser.  
 H301 Toxic if swallowed.  
 H302 Harmful if swallowed.  
 H302+H332 Harmful if swallowed or if inhaled.  
 H311 Toxic in contact with skin.

**Safety Data Sheet**

according to UK REACH Regulation

**Bouin Allen Fixative**

Revision date: 08.04.2024

Product code: 11641.xxxxx

Page 18 of 18

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H361f	Suspected of damaging fertility.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according EC regulation 1272/2008 (CLP): -

Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*