

Safety Data Sheet

according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Eosin 0,5 %, in ethanol 70 %

UFI: GW35-712G-600K-9ACM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Use as laboratory reagent. The product is intended for research, analysis and scientific education.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: MORPHISTO GmbH
Street: Schumannstr. 142/144
Place: D-63069 Offenbach

Telephone: +49 (0) 69 / 400 3019-60 Telefax: +49 (0) 69 / 400 3019-64

E-mail: info@morphisto.de Contact person: Morphisto GmbH

E-mail: gefahrstoffmanagement@morphisto.de

Internet: http://www.morphisto.de

1.4. Emergency telephone Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225 Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use sand, extinguishing powder or alcohol-resistant foam to extinguish.

Special labelling of certain mixtures

EUH208 Contains Eosin G. May produce an allergic reaction.



according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 2 of 17

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

| CAS No | Chemical name | | | Quantity | | |
|------------|--|---------------------------------------|------------------|-------------|--|--|
| | EC No | Index No | REACH No | | | |
| | Classification (GB CLP Re | egulation) | | | | |
| 64-17-5 | Ethanol | | | 55 - < 60 % | | |
| | 200-578-6 | 603-002-00-5 | 01-2119457610-43 | | | |
| | Flam. Liq. 2, Eye Irrit. 2; H | Flam. Liq. 2, Eye Irrit. 2; H225 H319 | | | | |
| 107-21-1 | ethanediol | | | 1 - < 5 % | | |
| | 203-473-3 | 603-027-00-1 | 01-2119456816-28 | | | |
| | Acute Tox. 4, STOT RE 2 | ; H302 H373 | • | | | |
| 78-93-3 | butanone | | | < 1 % | | |
| | 201-159-0 | 606-002-00-3 | 01-2119457290-43 | | | |
| | Flam. Liq. 2, Eye Irrit. 2, S | TOT SE 3; H225 H319 H336 EUH | 066 | | | |
| 17372-87-1 | Eosin G | | | < 1 % | | |
| | 241-409-6 | | 01-2120138551-62 | | | |
| | Eye Irrit. 2, Skin Sens. 1; I | H319 H317 | | | | |
| 64-19-7 | Acetic acid% | | | < 1 % | | |
| | 200-580-7 | 607-002-00-6 | 01-2119475328-30 | | | |
| | Flam. Liq. 3, Skin Corr. 1A; H226 H314 | | | | | |

Full text of H and EUH statements: see section 16.



Safety Data Sheet

according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 3 of 17

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity | | | | |
|------------|--|---|-------------|--|--|--|--|
| | Specific Conc. | Limits, M-factors and ATE | | | | | |
| 64-17-5 | 200-578-6 | Ethanol | 55 - < 60 % | | | | |
| | | inhalation: LC50 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg Eye Irrit. 2; H319: >= 50 - 100 | | | | | |
| 107-21-1 | 203-473-3 | ethanediol | 1 - < 5 % | | | | |
| | dermal: LD50 = >3500 mg/kg; oral: LD50 = 7712 mg/kg | | | | | | |
| 78-93-3 | 201-159-0 | butanone | < 1 % | | | | |
| | dermal: LD50 = >2000 mg/kg; oral: LD50 = 2054 mg/kg | | | | | | |
| 17372-87-1 | 241-409-6 | 241-409-6 Eosin G | | | | | |
| | oral: LD50 = 2344 mg/kg | | | | | | |
| 64-19-7 | 200-580-7 | 00-580-7 Acetic acid% | | | | | |
| | inhalation: LC50 = >40 mg/l (vapours); oral: LD50 = 3530 mg/kg Skin Corr. 1A; H314: >= 90 - 100 Skin Corr. 1B; H314: >= 25 - < 90 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25 | | | | | | |

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. In case of accident by inhalation: remove casualty to fresh air and keep at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. In case of skin irritation, seek medical treatment.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink 1 glass of of water. Let water be drunken in little sips (dilution effect). Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Acute effects: Mucous membrane irritation after eye contact or inhalation.

Delayed effects: Impairment of inhibitory functions of the central nervous system, skin redness, nausea after ingestion of large amounts.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Percutaneously absorbed and inhaled substance causes next to irritation of affected mucous membranes only an indicated impairment of the inhibitory functions of the central nervous system, clinically recognizable as the beginning of a euphoric stage. At the same time face and skin redness is caused by dilation of peripheral blood vessels in the body.

SECTION 5: Firefighting measures



according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 4 of 17

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder. Carbon dioxide (CO2). Dry extinguishing powder. alcohol resistant foam. Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

Vapours are heavier than air and will spread at floor level.

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Ventilate affected area.

Special danger of slipping by leaking/spilling product. (refer to chapter 8)

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Ventilate affected area. Treat the recovered material as prescribed in the section on waste disposal. Clear contaminated areas thoroughly.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

Wear personal protection equipment. (See section 8.) Use extractor hood (laboratory).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Heating causes rise in pressure with risk of bursting.



according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 5 of 17

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Remove contaminated, saturated clothing immediately. Always close containers tightly after the removal of product. Protect skin by using skin protective cream.

Further information on handling

General protection and hygiene measures: refer to chapter 8

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep/Store only in original container. Keep container tightly closed in a cool, well-ventilated place. Protect from direct sunlight.

Ensure adequate ventilation of the storage area. Concentrated vapours are heavier than air. Suitable material for Container: Stainless steel. (1.4301 (V2), 1.4401 (V4)); iron. solvent resistant plastics. Unsuitable materials for Container: Aluminium. Rubber. various plastics.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances or mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Recommended storage temperature: 15-25°C Protect against: UV-radiation/sunlight. heat. Cold.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m³ | fibres/ml | Category | Origin |
|----------|-----------------------------------|------|-------|-----------|---------------|--------|
| 64-19-7 | Acetic acid | 10 | 25 | | TWA (8 h) | WEL |
| | | 20 | 50 | | STEL (15 min) | WEL |
| 78-93-3 | Butan-2-one (methyl ethyl ketone) | 200 | 600 | | TWA (8 h) | WEL |
| | | 300 | 899 | | STEL (15 min) | WEL |
| 107-21-1 | Ethane-1,2-diol, vapour | 20 | 52 | | TWA (8 h) | WEL |
| | | 40 | 104 | | STEL (15 min) | WEL |
| 64-17-5 | Ethanol | 1000 | 1920 | | TWA (8 h) | WEL |

Biological Monitoring Guidance Values (EH40)

| CAS No | Substance | Parameter | Value | Test material | Sampling time |
|---------|-------------|-------------|-----------|---------------|---------------|
| 78-93-3 | Butan-2-one | butan-2-one | 70 µmol/L | urine | Post shift |



Safety Data Sheet

according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 6 of 17

DNEL/DMEL values

| CAS No | Substance | | | |
|--------------------------|----------------|----------------|----------|------------------|
| DNEL type | | Exposure route | Effect | Value |
| 64-17-5 | Ethanol | | | |
| Worker DNE | L, acute | inhalation | local | 1900 mg/m³ |
| Worker DNE | L, long-term | dermal | systemic | 343 mg/kg bw/day |
| Worker DNE | L, long-term | inhalation | systemic | 950 mg/m³ |
| Consumer D | NEL, acute | inhalation | local | 950 mg/m³ |
| Consumer D | NEL, long-term | dermal | systemic | 206 mg/kg bw/day |
| Consumer DNEL, long-term | | inhalation | systemic | 114 mg/m³ |
| Consumer D | NEL, long-term | oral | systemic | 87 mg/kg bw/day |
| 107-21-1 | ethanediol | | | |
| Worker DNE | L, long-term | inhalation | local | 35 mg/m³ |
| Worker DNE | L, long-term | dermal | systemic | 106 mg/kg bw/day |
| 64-19-7 | Acetic acid% | | | |
| Worker DNEL, long-term | | inhalation | local | 25 mg/m³ |
| Worker DNEL, acute | | inhalation | local | 25 mg/m³ |
| Consumer D | NEL, long-term | inhalation | local | 25 mg/m³ |
| Consumer D | NEL, acute | inhalation | local | 25 mg/m³ |



according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 7 of 17

PNEC values

| CAS No | Substance | |
|------------------------------------|---------------------------------------|------------|
| Environmen | tal compartment | Value |
| 64-17-5 | Ethanol | |
| Freshwater | | 0,96 mg/l |
| Freshwater | 2,75 mg/l | |
| Marine wate | r | 0,79 mg/l |
| Marine wate | r (intermittent releases) | 2,75 mg/l |
| Freshwater | sediment | 3,6 mg/kg |
| Marine sedir | ment | 2,9 mg/kg |
| Secondary p | poisoning | 0,72 mg/kg |
| Micro-organ | isms in sewage treatment plants (STP) | 580 mg/l |
| Soil | | 0,63 mg/kg |
| 107-21-1 | ethanediol | |
| Freshwater | | 10 mg/l |
| Marine wate | 1 mg/l | |
| Freshwater | sediment | 37 mg/kg |
| Marine sedir | ment | 3,7 mg/kg |
| Micro-organ | isms in sewage treatment plants (STP) | 199,5 mg/l |
| Soil | | 1,53 mg/kg |
| 64-19-7 | Acetic acid% | |
| Freshwater | | 3,058 mg/l |
| Freshwater (intermittent releases) | | |
| Marine wate | 0,306 mg/l | |
| Freshwater sediment | | |
| Marine sediment | | |
| Micro-organ | isms in sewage treatment plants (STP) | 85 mg/l |
| Soil | | 0,47 mg/kg |

8.2. Exposure controls







Appropriate engineering controls

Provide adequate ventilation.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Use extractor hood (laboratory).

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles. Tightly sealed safety glasses. EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the



according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 8 of 17

supplier of these gloves. In case of prolonged or frequently repeated skin contact:

Tested protective gloves are to be worn:

Suitable material:

Butyl rubber. (0,7 mm, Breakthrough time >=480 min, penetration time (maximum wearing period): 160 min): NBR (Nitrile rubber). (0,4 mm, Breakthrough time >=120 min, penetration time (maximum wearing period): 40 min)

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing Protective clothing.

(flame-retardant)

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Insufficient ventilation.

exceeding exposure limit values

generation/formation of aerosols

Suitable respiratory protective equipment:

gas filtering equipment (EN 141). Type: a

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: pink
Odour: alcoholic

Melting point/freezing point:

Boiling point or initial boiling point and

Ethanol: 78 °C

boiling range:

Flammability: not determined Lower explosion limits: Ethanol: 3,4 vol. % Upper explosion limits: Ethanol: 15 vol. % Flash point: ~20 °C Ethanol: 425 °C Auto-ignition temperature: Decomposition temperature: not determined pH-Value: not determined Viscosity / kinematic: not determined Water solubility: miscible.

Solubility in other solvents

miscible.

Partition coefficient n-octanol/water: not determined



Safety Data Sheet

according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 9 of 17

Vapour pressure: Ethanol: 59 hPa

(at 20 °C)

Vapour pressure: Ethanol: 280 hPa

(at 50 °C)

Density (at 20 °C): Ethanol: 0,88-0,89 g/cm³ Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Sustaining combustion: Sustaining combustion

Self-ignition temperature

Gas: not determined

Oxidizing properties

none

Other safety characteristics

Evaporation rate: not determined Solvent separation test: not determined Solvent content: not determined Solid content: not determined Sublimation point: not determined Softening point: not determined Pour point: not determined Viscosity / dynamic: not determined not determined Flow time:

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable. No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Explosion risk in contact with: Oxidizing agents, strong. nitric acid. Hydrogenium peroxide. Exothermic reactions with: Alkali metals. Alkaline earth metals. Reducing agents, strong.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Keep away from heat. Protect from direct sunlight. Protect from moisture. In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting. Recommended storage temperature: < 40 °C

10.5. Incompatible materials

Strong acid. Oxidizing agents. Alkali metals. Alkaline earth metals. Peroxides. phosphorus oxides. Nitrogen oxides (NOx). Hydrogenium peroxide. Nitric acid. hydrochloric acid. Sulfuric acid. Perchlorates. Chromium oxides. Acid chlorides.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation



Safety Data Sheet

according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 10 of 17

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 13850 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

| CAS No | Chemical name | | | | | |
|------------|-------------------------|---------------|----------|----------------------|----------------|--------|
| | Exposure route | Dose | | Species | Source | Method |
| 64-17-5 | Ethanol | | | | | |
| | oral | LD50 mg/kg | >5000 | Rat | ECHA Dossier | |
| | dermal | LD50 mg/kg | >2000 | Rabbit | ECHA Dossier | |
| | inhalation (4 h) vapour | LC50 mg/l | 124,7 | Rat | ECHA Dossier | |
| 107-21-1 | ethanediol | | | | | |
| | oral | LD50 mg/kg | 7712 | Rat | ECHA | |
| | dermal | LD50 mg/kg | >3500 | Mouse | ECHA | |
| 78-93-3 | butanone | | | | | |
| | oral | LD50 mg/kg | 2054 | Ratte | SDB Lieferant | |
| | dermal | LD50 mg/kg | >2000 | Rabbit | ECHA Dossier | |
| 17372-87-1 | Eosin G | _ | | | | |
| | oral | LD50 mg/kg | 2344 | Rat, male and female | suppliers SDS. | |
| 64-19-7 | Acetic acid% | | | | | |
| | oral | LD50 mg/kg | 3530 | Rat | GESTIS | |
| | inhalation (4 h) vapour | LC50 | >40 mg/l | Rat | suppliers SDS. | |

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Contains Eosin G. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.



Safety Data Sheet

according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 11 of 17

Other information

Depending on the ingested quantity the following symptoms can be induced: a reduction of inhibitions, euphoria but also dysphoria, aggressiveness, impaired motoric skills, impaired responsiveness, blurred vision and fatigue.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | | | |
|----------|--------------------------|---------------|----------|-----------|--------------------------------------|--------------|----------|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source | Method |
| 64-17-5 | Ethanol | | | | | | |
| | Acute fish toxicity | LC50 mg/l | 14200 | 96 h | Pimephales promelas (fathead minnow) | ECHA Dossier | |
| | Acute algae toxicity | ErC50 | 275 mg/l | 72 h | Chlorella vulgaris | ECHA Dossier | |
| | Acute crustacea toxicity | EC50 mg/l | 5012 | 48 h | Ceriodaphnia dubia (water flea) | ECHA Dossier | |
| | Crustacea toxicity | NOEC | 9,6 mg/l | 9 d | Daphnia magna | ECHA Dossier | |
| 107-21-1 | ethanediol | | | | | | |
| | Acute fish toxicity | LC50 mg/l | >17000 | 96 h | Oncorhynchus mykiss (Rainbow trout) | ECHA | |
| | Acute algae toxicity | ErC50 mg/l | >6500 | 96 h | Selenastrum capricornutum | ECHA | |
| | Acute crustacea toxicity | EC50 mg/l | >100 | 48 h | Daphnia magna (Big water flea) | ECHA | |
| | Fish toxicity | NOEC mg/l | >1500 | 28 d | Oncorhynchus mykiss (Rainbow trout) | ECHA | |
| | Crustacea toxicity | NOEC mg/l | >15000 | 21 d | Daphnia magna (Big water flea) | ECHA | |
| 78-93-3 | butanone | | | | | | |
| | Acute fish toxicity | LC50 mg/l | 2993 | 96 h | Pimephales promelas | ECHA Dossier | OECD 203 |
| | Acute algae toxicity | ErC50 mg/l | 1972 | 72 h | Pseudokirchnerella subcapitata | ECHA Dossier | OECD 201 |
| | Acute crustacea toxicity | EC50 | 308 mg/l | 48 h | Daphnia magna | ECHA Dossier | OECD 202 |
| 64-19-7 | Acetic acid% | | | | | | |
| | Acute fish toxicity | LC50 mg/l | >300 | 96 h | Oncorhynchus mykiss | ECHA Dossier | |
| | Acute algae toxicity | ErC50 mg/l | >300 | 72 h | Skeletonema costatum | ECHA Dossier | |
| | Acute crustacea toxicity | EC50 mg/l | >300 | 48 h | Daphnia magna | ECHA Dossier | |

12.2. Persistence and degradability



Safety Data Sheet

according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 12 of 17

| CAS No | Chemical name | | | | |
|----------|--|--------|----|----------------|--|
| | Method | Value | d | Source | |
| | Evaluation | - | | | |
| 64-17-5 | Ethanol | | | | |
| | other guideline | 84% | 20 | ECHA Dossier | |
| | Biodegradable. | | | | |
| 107-21-1 | ethanediol | | | | |
| | Biodegradability | 83-96% | 14 | | |
| | Readily biodegradable (according to OECD criteria). | | | | |
| 78-93-3 | butanone | | | | |
| | | 98% | 28 | ECHA Dossier | |
| | Readily biodegradable (according to OECD criteria). | | | | |
| 64-19-7 | Acetic acid% | | | | |
| | Other guideline | 95% | 5 | suppliers SDS. | |
| | Easily biodegradable (concerning to the criteria of the OECD |) | | | |

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|------------|---------------|---------|
| 64-17-5 | Ethanol | -0,31 |
| 107-21-1 | ethanediol | -1,36 |
| 78-93-3 | butanone | 0,3 |
| 17372-87-1 | Eosin G | 6,92 |
| 64-19-7 | Acetic acid% | -0,17 |

BCF

| CAS No | Chemical name | BCF | Species | Source |
|---------|---------------|------|---------|--------|
| 64-19-7 | Acetic acid% | 3,16 | | |

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

The product has not been tested.

Further information

Avoid release to the environment. Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:



Safety Data Sheet

according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 13 of 17

List of Wastes Code - residues/unused products

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances,

including mixtures of laboratory chemicals; hazardous waste

List of Wastes Code - used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances,

including mixtures of laboratory chemicals; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es): 3



according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 14 of 17

14.4. Packing group: II Hazard label: 3



Marine pollutant:

Special Provisions:

Limited quantity:

Excepted quantity:

Excepted quantity:

Excepted F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: A3 A58 A180

Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. Refer to section 6-8

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): not determined 2004/42/EC (VOC): not determined

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS

(SEVESO III):

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water



according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 15 of 17

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Ethanol ethanediol

butanone

Eosin G

Acetic acid...%

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,16.

Rev. 2,0; 23.05.2023, Individual safety data sheet based on 11439_collect

Rev. 2,1; 23.08.2023; general adjustment(s)

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

AGW: Arbeitsplatzgrenzwert AVV: Abfallverzeichnisverordnung CAS Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

ECHA: European Chemicals Agency EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level

NLP: No-Longer Polymers

N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern TRGS Technische Regeln fuer Gefahrstoffe

UN: United Nations

VOC: Volatile Organic Compounds



according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 16 of 17

VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrdungsklasse

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOFC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules MFAG: Medical First Aid Guide

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to GB CLP Regulation

| Classification | Classification procedure |
|--------------------|--------------------------|
| Flam. Liq. 2; H225 | On basis of test data |
| Eye Irrit. 2; H319 | Calculation method |

Relevant H and EUH statements (number and full text)

| H225 | Highly flammable liquid and vapour. |
|------|--|
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |

H373 May cause damage to organs through prolonged or repeated exposure.

EUH066 Repeated exposure may cause skin dryness or cracking. EUH208 Contains Eosin G. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according to Regulation (EC) No 1272/2008 [CLP]

- Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.



Safety Data Sheet

according to UK REACH Regulation

Eosin 0,5 %, in ethanol 70 %

Revision date: 23.08.2023 Product code: 13044.xxxxx Page 17 of 17

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)