

according to UK REACH Regulation

### Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 1 of 16

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Eosin 0,5 %, alcoholic 90 %, acid

UFI: 15YP-11Q9-A00X-4X32

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Use as laboratory reagent. The product is intended for research, analysis and scientific education.

#### Uses advised against

Any non-intended use.

### 1.3. Details of the supplier of the safety data sheet

Company name: MORPHISTO GmbH
Street: Schumannstr. 142/144
Place: D-63069 Offenbach

Telephone: +49 (0) 69 / 400 3019-60 Telefax: +49 (0) 69 / 400 3019-64

E-mail: info@morphisto.de Contact person: Morphisto GmbH

E-mail: gefahrstoffmanagement@morphisto.de

Internet: http://www.morphisto.de

**1.4. Emergency telephone** Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

number:

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### **GB CLP Regulation**

Flam. Liq. 2; H225 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

### **GB CLP Regulation**

#### Hazard components for labelling

propan-1-ol

Signal word: Danger

Pictograms:





### **Hazard statements**

H225 Highly flammable liquid and vapour. H318 Causes serious eye damage.

### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.



according to UK REACH Regulation

Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 2 of 16

P370+P378 In case of fire: Use sand, extinguishing powder or alcohol-resistant foam to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

EUH208 Contains Eosin G. May produce an allergic reaction.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





**Hazard statements** 

H318

**Precautionary statements** 

P280-P305+P351+P338-P310

#### 2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

### **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

#### **Hazardous components**

CAS No	Chemical name	Quantity			
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation	on)			
64-17-5	Ethanol			80 - < 85 %	
	200-578-6	603-002-00-5	01-2119457610-43		
	Flam. Liq. 2, Eye Irrit. 2; H225 H	319			
71-23-8	propan-1-ol			1 - < 5 %	
	200-746-9	603-003-00-0	01-2119486761-29		
	Flam. Liq. 2, Eye Dam. 1, STOT	SE 3; H225 H318 H336			
78-93-3	butanone			< 1 %	
	201-159-0	606-002-00-3	01-2119457290-43		
	Flam. Liq. 2, Eye Irrit. 2, STOT S	E 3; H225 H319 H336 EUH	066		
64-19-7	Acetic acid%			< 1 %	
	200-580-7	607-002-00-6	01-2119475328-30		
	Flam. Liq. 3, Skin Corr. 1A; H226	6 H314			
17372-87-1	Eosin G			< 1 %	
	241-409-6		01-2120138551-62		
	Eye Irrit. 2, Skin Sens. 1; H319 H317				

Full text of H and EUH statements: see section 16.



## **Safety Data Sheet**

according to UK REACH Regulation

### Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 3 of 16

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Conc.	Limits, M-factors and ATE				
64-17-5	200-578-6	Ethanol	80 - < 85 %			
		50 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 it. 2; H319: >= 50 - 100				
71-23-8	200-746-9	propan-1-ol	1 - < 5 %			
	dermal: LD50 = 40321 mg/kg					
78-93-3	201-159-0	butanone	< 1 %			
	dermal: LD50 = >2000 mg/kg; oral: LD50 = 2054 mg/kg					
64-19-7	200-580-7	Acetic acid%	< 1 %			
		50 = >40 mg/l (vapours); oral: LD50 = 3530 mg/kg				
17372-87-1	241-409-6	Eosin G	< 1 %			
	oral: LD50 = 2344 mg/kg					

#### **Further Information**

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

Remove affected person from the danger area and lay down. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

### After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

#### After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. In case of skin irritation, seek medical treatment.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

### After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Seek medical advice.

### 4.2. Most important symptoms and effects, both acute and delayed

Acute effects: Mucous membrane irritation after eye contact or inhalation.

Delayed effects: Impairment of inhibitory functions of the central nervous system, skin redness, nausea after ingestion of large amounts.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Percutaneously absorbed and inhaled substance causes next to irritation of affected mucous membranes only an indicated impairment of the inhibitory functions of the central nervous system, clinically recognizable as the beginning of a euphoric stage. At the same time face and skin redness is caused by dilation of peripheral blood vessels in the body.

## **SECTION 5: Firefighting measures**



### **Safety Data Sheet**

according to UK REACH Regulation

### Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 4 of 16

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Water spray jetCarbon dioxide (CO2) FoamExtinguishing powder Carbon dioxide (CO2). Dry extinguishing powder. alcohol resistant foam. Atomized water.

#### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Highly flammable Vapours can form explosive mixtures with air. Vapours are heavier than air and will spread at floor level.In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2).

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Special danger of slipping by leaking/spilling product. (refer to chapter 8)

### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

## For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### Other information

Ventilate affected area. Treat the recovered material as prescribed in the section on waste disposal. Clear contaminated areas thoroughly.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

Wear personal protection equipment. (See section 8.) Use extractor hood (laboratory).

### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.Flammable vapours can accumulate in head space of closed systems. Heating causes rise in pressure with risk of bursting.



according to UK REACH Regulation

### Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 5 of 16

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product. Protect skin by using skin protective cream.

## Further information on handling

General protection and hygiene measures: refer to chapter 8

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep/Store only in original container. Protect from direct sunlight. Concentrated vapours are heavier than air.Suitable material for Container: Stainless steel. (1.4301 (V2), 1.4401 (V4)); iron. solvent resistant plastics.Unsuitable materials for Container: Aluminium. Rubber. various plastics.

### Hints on joint storage

Do not store together with: Oxidizing agent Pyrophoric or self-heating substances Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances or mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

### Further information on storage conditions

Recommended storage temperature: 15-25°C Protect against: UV-radiation/sunlight. heat. Cold.

### 7.3. Specific end use(s)

See section 1.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
64-19-7	Acetic acid	10	25		TWA (8 h)	WEL
		20	50		STEL (15 min)	WEL
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
71-23-8	Propan-1-ol	200	500		TWA (8 h)	WEL
ı		250	625		STEL (15 min)	WEL
	•					1

## **Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift



according to UK REACH Regulation

# Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 6 of 16

# **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64-17-5	Ethanol			
Worker DNEL,	acute	inhalation	local	1900 mg/m³
Worker DNEL,	long-term	dermal	systemic	343 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	950 mg/m³
Consumer DNE	EL, acute	inhalation	local	950 mg/m³
Consumer DNE	EL, long-term	dermal	systemic	206 mg/kg bw/day
Consumer DNE	EL, long-term	inhalation	systemic	114 mg/m³
Consumer DNE	EL, long-term	oral	systemic	87 mg/kg bw/day
64-19-7	Acetic acid%			
Worker DNEL, long-term		inhalation	local	25 mg/m³
Worker DNEL, acute		inhalation	local	25 mg/m³
Consumer DNEL, long-term		inhalation	local	25 mg/m³
Consumer DNE	EL, acute	inhalation	local	25 mg/m³

## **PNEC** values

CAS No	Substance			
Environmen	tal compartment	Value		
64-17-5	64-17-5 Ethanol			
Freshwater		0,96 mg/l		
Freshwater	(intermittent releases)	2,75 mg/l		
Marine wate	r	0,79 mg/l		
Marine wate	r (intermittent releases)	2,75 mg/l		
Freshwater	sediment	3,6 mg/kg		
Marine sedir	nent	2,9 mg/kg		
Secondary p	0,72 mg/kg			
Micro-organisms in sewage treatment plants (STP)		580 mg/l		
Soil		0,63 mg/kg		
64-19-7	Acetic acid%			
Freshwater		3,058 mg/l		
Freshwater	(intermittent releases)	30,58 mg/l		
Marine water		0,306 mg/l		
Freshwater sediment		11,36 mg/kg		
Marine sediment		1,136 mg/kg		
Micro-organisms in sewage treatment plants (STP)				
Soil		0,47 mg/kg		

# 8.2. Exposure controls









### **Safety Data Sheet**

according to UK REACH Regulation

### Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 7 of 16

#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Use extractor hood (laboratory).

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Suitable eye protection: goggles. Tightly sealed safety glasses. EN 166

### **Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. In case of prolonged or frequently repeated skin contact:

Tested protective gloves are to be worn:

Suitable material:

Butyl rubber. (0,7 mm, Breakthrough time >=480 min, penetration time (maximum wearing period): 160 min): NBR (Nitrile rubber). (0,4 mm, Breakthrough time >=120 min, penetration time (maximum wearing period): 40 min)

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing Protective clothing. (flame-retardant)

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Insufficient ventilation.

exceeding exposure limit values

generation/formation of aerosols

Suitable respiratory protective equipment:

gas filtering equipment (EN 141). Type: a

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

#### Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: orange - pink
Odour: characteristic

Melting point/freezing point: not determined



according to UK REACH Regulation

### Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 8 of 16

Boiling point or initial boiling point and Ethanol: 78 °C

boiling range:

Flammability: not determined Lower explosion limits: 3,1 vol. % 27,7 vol. % Upper explosion limits: Flash point: ~20 °C Auto-ignition temperature: 400 °C Decomposition temperature: not determined pH-Value: not determined Viscosity / kinematic: not determined Water solubility: miscible.

(at 20 °C)

Solubility in other solvents

miscible.

Partition coefficient n-octanol/water: not determined Vapour pressure: not determined

(at 20 °C)

Density (at 20 °C): 0,81 g/cm³
Relative vapour density: not determined

#### 9.2. Other information

### Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Sustaining combustion: Sustaining combustion

Self-ignition temperature

Gas: not determined

Oxidizing properties

none

## Other safety characteristics

Evaporation rate: not determined Solvent separation test: not determined Solvent content: not determined Solid content: not determined Sublimation point: not determined Softening point: not determined Pour point: not determined Viscosity / dynamic: not determined Flow time: not determined

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Highly flammableNo information available.

## 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

Explosion risk in contact with: Oxidizing agents, strong. nitric acid. Hydrogenium peroxide. Exothermic reactions with: Alkali metals. Alkaline earth metals. Reducing agents, strong.

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Keep away from heat. Protect from direct sunlight. Protect from moisture.



### **Safety Data Sheet**

according to UK REACH Regulation

## Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 9 of 16

In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting. Recommended storage temperature: < 40 °C

### 10.5. Incompatible materials

Strong acid. Oxidizing agents. Alkali metals. Alkaline earth metals. Peroxides. phosphorus oxides. Nitrogen oxides (NOx). Hydrogenium peroxide. Nitric acid. hydrochloric acid. Sulfuric acid. Perchlorates. Chromium oxides. Acid chlorides.

# 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2).

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

	Thou, a might						
CAS No	Chemical name				_		
	Exposure route	Dose		Species	Source	Method	
64-17-5	Ethanol						
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier		
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier		
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	ECHA Dossier		
71-23-8	propan-1-ol						
	dermal	LD50 mg/kg	40321	Kaninchen			
78-93-3	butanone						
	oral	LD50 mg/kg	2054	Ratte	SDB Lieferant		
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier		
64-19-7	Acetic acid%						
	oral	LD50 mg/kg	3530	Rat	GESTIS		
	inhalation (4 h) vapour	LC50	>40 mg/l	Rat	suppliers SDS.		
17372-87-1	Eosin G						
	oral	LD50 mg/kg	2344	Rat, male and female	suppliers SDS.		

#### Irritation and corrosivity

Causes serious eye damage.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Contains Eosin G. May produce an allergic reaction.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

## Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 10 of 16

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

### **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

#### Other information

Depending on the ingested quantity the following symptoms can be induced: a reduction of inhibitions, euphoria but also dysphoria, aggressiveness, impaired motoric skills, impaired responsiveness, blurred vision and fatigue.

#### **Further information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
64-17-5	Ethanol	Ethanol						
	Acute fish toxicity	LC50 mg/l	14200	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier		
	Acute algae toxicity	ErC50	275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier		
	Acute crustacea toxicity	EC50 mg/l	5012	48 h	Ceriodaphnia dubia (water flea)	ECHA Dossier		
	Crustacea toxicity	NOEC	9,6 mg/l	9 d	Daphnia magna	ECHA Dossier		
71-23-8	propan-1-ol							
	Acute fish toxicity	LC50 mg/l	4555	96 h		ECHA Dossier		
	Acute crustacea toxicity	EC50 mg/l	3644	48 h		ECHA Dossier		
78-93-3	butanone							
	Acute fish toxicity	LC50 mg/l	2993	96 h	Pimephales promelas	ECHA Dossier	OECD 203	
	Acute algae toxicity	ErC50 mg/l	1972	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	OECD 201	
	Acute crustacea toxicity	EC50	308 mg/l	48 h	Daphnia magna	ECHA Dossier	OECD 202	
64-19-7	Acetic acid%							
	Acute fish toxicity	LC50 mg/l	>300	96 h	Oncorhynchus mykiss	ECHA Dossier		
	Acute algae toxicity	ErC50 mg/l	>300	72 h	Skeletonema costatum	ECHA Dossier		
	Acute crustacea toxicity	EC50 mg/l	>300	48 h	Daphnia magna	ECHA Dossier		

### 12.2. Persistence and degradability

The product has not been tested.



## **Safety Data Sheet**

according to UK REACH Regulation

### Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 11 of 16

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation		-	
64-17-5	Ethanol			
	other guideline	84%	20	ECHA Dossier
	Biodegradable.			
78-93-3	butanone			
		98%	28	ECHA Dossier
	Readily biodegradable (according to OECI	D criteria).		
64-19-7	Acetic acid%			
	Other guideline	95%	5	suppliers SDS.
	Easily biodegradable (concerning to the criteria of the OECD)			

#### 12.3. Bioaccumulative potential

The product has not been tested.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	Ethanol	-0,31
71-23-8	propan-1-ol	0,2
78-93-3	butanone	0,3
64-19-7	Acetic acid%	-0,17
17372-87-1	Eosin G	6,92

### **BCF**

CAS No	Chemical name	BCF	Species	Source
64-19-7	Acetic acid%	3,16		

#### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

The product has not been tested.

#### **Further information**

Avoid release to the environment. Do not allow to enter into surface water or drains.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

## List of Wastes Code - residues/unused products



according to UK REACH Regulation

### Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 12 of 16

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances,

including mixtures of laboratory chemicals; hazardous waste

List of Wastes Code - used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals: laboratory chemicals, consisting of or containing hazardous substances.

including mixtures of laboratory chemicals: hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es): 3
14.4. Packing group:



according to UK REACH Regulation

### Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 13 of 16

Hazard label:



Marine pollutant:

Special Provisions:

Limited quantity:

Excepted quantity:

Excepted quantity:

Excepted quantity:

E2

EmS:

F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: A3 A58 A180

Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. Refer to section 6-8

14.7. Maritime transport in bulk according to IMO instruments

not relevant

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): not determined 2004/42/EC (VOC): not determined

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS

(SEVESO III):

#### **Additional information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

#### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water



## **Safety Data Sheet**

according to UK REACH Regulation

### Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 14 of 16

#### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Ethanol propan-1-ol butanone

Acetic acid...%

Eosin G

### **SECTION 16: Other information**

## Changes

This data sheet contains changes from the previous version in section(s): 2,3,9,15,16.

Rev. 2,0, 04.06.2023, Individual safety data sheet based on 11503\_collect

Rev. 2,1; 24.08.2023; general revision / adjustment section 2.2

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

AGW: Arbeitsplatzgrenzwert AVV: Abfallverzeichnisverordnung CAS Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: dav(s)

EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European LIst of Notified Chemical Substances

ECHA: European Chemicals Agency EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level

NLP: No-Longer Polymers N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail )

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern TRGS Technische Regeln fuer Gefahrstoffe

**UN: United Nations** 

VOC: Volatile Organic Compounds



#### according to UK REACH Regulation

### Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 15 of 16

VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrdungsklasse

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

**UN: United Nations** 

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOFC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules MFAG: Medical First Aid Guide

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Highly flammable liquid and vapour.

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Dam. 1; H318	Calculation method

### Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cra

EUH066 Repeated exposure may cause skin dryness or cracking. EUH208 Contains Eosin G. May produce an allergic reaction.

### **Further Information**

H225

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according to Regulation (EC) No 1272/2008 [CLP]

- Classification procedure:

Health hazards: Calculation method. Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.



# **Safety Data Sheet**

according to UK REACH Regulation

## Eosin 0,5 %, alcoholic 90 %, acid

Revision date: 24.08.2023 Product code: 19127.xxxxx Page 16 of 16

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)