

according to UK REACH Regulation

## Ethanol 96 %, denatured (MEK/IPA/BTX)

Revision date: 25.01.2024 Product code: 11470.xxxxx Page 1 of 15

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Ethanol 96 %, denatured (MEK/IPA/BTX)

UFI: 9SR0-J1NN-300N-3052

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Use as laboratory reagent

### Uses advised against

Any non-intended use.

## 1.3. Details of the supplier of the safety data sheet

Company name: MORPHISTO GmbH
Street: Schumannstr. 142/144
Place: D-63069 Offenbach

Telephone: +49 (0) 69 / 400 3019-60 Telefax: +49 (0) 69 / 400 3019-64

E-mail: info@morphisto.de Contact person: Morphisto GmbH

E-mail: gefahrstoffmanagement@morphisto.de

Internet: http://www.morphisto.de

1.4. Emergency telephone Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

number:

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### **GB CLP Regulation**

Flam. Liq. 2; H225 Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

## **GB CLP Regulation**

Signal word: Danger

Pictograms:





#### **Hazard statements**

H225 Highly flammable liquid and vapour.H319 Causes serious eye irritation.

# **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use sand, extinguishing powder or alcohol-resistant foam to extinguish.

### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger



according to UK REACH Regulation

## Ethanol 96 %, denatured (MEK/IPA/BTX)

Revision date: 25.01.2024 Product code: 11470.xxxxx Page 2 of 15

### Pictograms:





## 2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

## Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Reg	ulation)	•		
64-17-5	ethanol			95 - < 100 %	
	200-578-6	603-002-00-5	01-2119457610-43		
	Flam. Liq. 2, Eye Irrit. 2; H2	25 H319			
67-63-0	2-propanol			< 1 %	
	200-661-7	603-117-00-0	01-2119457558-25		
	Flam. Liq. 2, Eye Irrit. 2, ST	OT SE 3; H225 H319 H336			
78-93-3	butanone			< 1 %	
	201-159-0	606-002-00-3	01-2119457290-43		
	Flam. Liq. 2, Eye Irrit. 2, ST	OT SE 3; H225 H319 H336 EUH	066		
3734-33-6	Denatoniumbenzoate			< 1 %	
	223-095-2				
	Acute Tox. 4, Acute Tox. 4, H412	Skin Irrit. 2, Eye Dam. 1, Aquatic	Chronic 3; H332 H302 H315 H318		

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc	Specific Conc. Limits, M-factors and ATE			
64-17-5	200-578-6	ethanol	95 - < 100 %		
		:50 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 rit. 2; H319: >= 50 - 100			
67-63-0	200-661-7	2-propanol	< 1 %		
	dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg				
78-93-3	201-159-0	butanone	< 1 %		
	dermal: LD50 = >2000 mg/kg; oral: LD50 = 2054 mg/kg				
3734-33-6	223-095-2	Denatoniumbenzoate	< 1 %		
		E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = oral: ATE = 500 mg/kg			



according to UK REACH Regulation

## Ethanol 96 %, denatured (MEK/IPA/BTX)

Revision date: 25.01.2024 Product code: 11470.xxxxx Page 3 of 15

#### **Further Information**

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### After inhalation

Provide fresh air. In case of accident by inhalation: remove casualty to fresh air and keep at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

#### After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. In case of skin irritation, seek medical treatment.

### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

### After ingestion

Rinse mouth immediately and drink plenty of water. Seek medical advice.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Percutaneously absorbed and inhaled substance causes next to irritation of affected mucous membranes only an indicated impairment of the inhibitory functions of the central nervous system, clinically recognizable as the beginning of a euphoric stage. At the same time face and skin redness is caused by dilation of peripheral blood vessels in the body.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Dry extinguishing powder. alcohol resistant foam. Atomized water.

### 5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

Vapours are heavier than air and will spread at floor level.

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2).

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Do not inhale explosion and combustion gases.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Remove all sources of ignition. Ventilate affected area.

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

Special danger of slipping by leaking/spilling product.

Wear personal protection equipment. (refer to chapter 8)

### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.



## **Safety Data Sheet**

according to UK REACH Regulation

## Ethanol 96 %, denatured (MEK/IPA/BTX)

Revision date: 25.01.2024 Product code: 11470.xxxxx Page 4 of 15

Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal.

Clear contaminated areas thoroughly.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Flammable vapours can accumulate in head space of closed systems. Heating causes rise in pressure with risk of bursting.

## Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. Always close containers tightly after the removal of product. When using do not eat, drink or smoke. Protect skin by using skin protective cream.

### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep/Store only in original container. Protect from direct sunlight.

Ensure adequate ventilation of the storage area. Concentrated vapours are heavier than air.

Suitable material for Container: Stainless steel. (1.4301 (V2), 1.4401 (V4)); iron. solvent resistant plastics.

Unsuitable materials for Container: Aluminium. Rubber. various plastics.

#### Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances or mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

### Further information on storage conditions

storage temperature: 15-25 °C

### 7.3. Specific end use(s)

Use as laboratory reagent

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters



according to UK REACH Regulation

# Ethanol 96 %, denatured (MEK/IPA/BTX)

Revision date: 25.01.2024 Product code: 11470.xxxxx Page 5 of 15

## **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

## **Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

## **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64-17-5	ethanol			
Worker DNEL	acute	inhalation	local	1900 mg/m³
Worker DNEL	long-term	dermal	systemic	343 mg/kg bw/day
Worker DNEL	long-term	inhalation	systemic	950 mg/m³
Consumer DN	EL, acute	inhalation	local	950 mg/m³
Consumer DN	EL, long-term	dermal	systemic	206 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	114 mg/m³
Consumer DN	EL, long-term	oral	systemic	87 mg/kg bw/day
67-63-0	2-propanol			
Worker DNEL	long-term	inhalation	systemic	500 mg/m³
Consumer DN	EL, long-term	inhalation	systemic	89 mg/m³
Worker DNEL	long-term	dermal	systemic	888 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	26 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
78-93-3	butanone			
Worker DNEL	long-term	inhalation	systemic	600 mg/m³
Worker DNEL	long-term	dermal	systemic	1161 mg/kg bw/day



according to UK REACH Regulation

## Ethanol 96 %, denatured (MEK/IPA/BTX)

Revision date: 25.01.2024 Product code: 11470.xxxxx Page 6 of 15

#### **PNEC values**

CAS No	Substance	
Environment	tal compartment	Value
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (	(intermittent releases)	2,75 mg/l
Marine wate	r	0,79 mg/l
Marine wate	r (intermittent releases)	2,75 mg/l
Freshwater	sediment	3,6 mg/kg
Marine sedir	ment	2,9 mg/kg
Secondary p	poisoning	0,72 mg/kg
Micro-organi	isms in sewage treatment plants (STP)	580 mg/l
Soil		0,63 mg/kg
67-63-0	2-propanol	
Freshwater		140,9 mg/l
Marine wate	г	140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary p	poisoning	160 mg/kg
Soil		28 mg/kg
78-93-3	butanone	
Freshwater		55,8 mg/l
Freshwater (intermittent releases)		55,8 mg/l
Marine water		55,8 mg/l
Freshwater sediment		284,7 mg/kg
Marine sediment		284,7 mg/kg
Micro-organi	isms in sewage treatment plants (STP)	709 mg/l
Soil		22,5 mg/kg

### 8.2. Exposure controls



## Individual protection measures, such as personal protective equipment

## Eye/face protection

Wear eye/face protection. Tightly sealed safety glasses. EN 166

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. In case of prolonged or frequently repeated skin contact:

Tested protective gloves are to be worn:

Suitable material:

Butyl rubber. (0,7 mm, Breakthrough time >=480 min, penetration time (maximum wearing period): 160 min): NBR (Nitrile rubber). (0,4 mm, Breakthrough time >=120 min, penetration time (maximum wearing period): 40



according to UK REACH Regulation

## Ethanol 96 %, denatured (MEK/IPA/BTX)

Revision date: 25.01.2024 Product code: 11470.xxxxx Page 7 of 15

min)

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

#### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing. Protective clothing. (fire retardant.) Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

### Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Insufficient ventilation.

exceeding exposure limit values

generation/formation of aerosols

Suitable respiratory protective equipment:

gas filtering equipment (EN 141). Type: a

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

The wearing time limitations according to GefStoffV in conjunction with the rules for the use of respiratory protective devices (BGR 190) must be observed.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: alcoholic

Melting point/freezing point:

Boiling point or initial boiling point and

78 °C

boiling range:

Flammability: No data available Lower explosion limits: 2.5 vol. % Upper explosion limits: 15 vol. % 12 °C Flash point: 400 °C Auto-ignition temperature: Decomposition temperature: not determined pH-Value: not determined Viscosity / kinematic: not determined Water solubility: completely miscible

(at 20 °C)

Vapour pressure: 58 hPa

(at 20 °C)

Density (at 20 °C): 0,8-0,9 g/cm<sup>3</sup>

### 9.2. Other information

### Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.



## **Safety Data Sheet**

according to UK REACH Regulation

## Ethanol 96 %, denatured (MEK/IPA/BTX)

Revision date: 25.01.2024 Product code: 11470.xxxxx Page 8 of 15

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Highly flammable.

### 10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidizing agent Alkali metals. Aluminium. Nitric acid. Sulphuric acid. Nitric oxides. Hydrogen peroxide. Barium perchlorate. Lead chlorate. Lead perchlorate. Chromosulphuric acid. Dichlorohexoxide. Magnesium powder. Sodium hypochlorite. Perchloric acid. Permanganic acid. Zinc diethyl.

## 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Keep away from heat. Protect from direct sunlight. Protect from moisture. In use may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

## 10.5. Incompatible materials

No data available

### 10.6. Hazardous decomposition products

Formation of carbon dioxide Carbon monoxide

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in GB CLP Regulation

## Acute toxicity

Based on available data, the classification criteria are not met.

## ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



## **Safety Data Sheet**

according to UK REACH Regulation

## Ethanol 96 %, denatured (MEK/IPA/BTX)

Revision date: 25.01.2024 Product code: 11470.xxxxx Page 9 of 15

CAS No	Chemical name	Chemical name						
	Exposure route	Dose		Species	Source	Method		
64-17-5	ethanol			•	·			
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier			
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier			
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	ECHA Dossier			
67-63-0	2-propanol							
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier			
	dermal	LD50 mg/kg	>5000	Rabbit	ECHA Dossier			
78-93-3	butanone							
	oral	LD50 mg/kg	2054	Ratte	SDB Lieferant			
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier			
3734-33-6	Denatoniumbenzoate							
	oral	ATE mg/kg	500					
	dermal	LD50 mg/kg	>2000	Rat	suppliers SDS.			
	inhalation vapour	ATE	11 mg/l					
	inhalation dust/mist	ATE	1,5 mg/l					

### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

# 11.2. Information on other hazards

### **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

# Ethanol 96 %, denatured (MEK/IPA/BTX)

Revision date: 25.01.2024 Product code: 11470.xxxxx Page 10 of 15

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method		
64-17-5	ethanol								
	Acute fish toxicity	LC50 mg/l	14200	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier			
	Acute algae toxicity	ErC50	275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier			
	Acute crustacea toxicity	EC50 mg/l	5012	48 h	Ceriodaphnia dubia (water flea)	ECHA Dossier			
	Crustacea toxicity	NOEC	9,6 mg/l	9 d	Daphnia magna	ECHA Dossier			
67-63-0	2-propanol								
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas	ECHA Dossier	OECD Guideline 203		
	Acute algae toxicity	ErC50 mg/l	1800	96 h	Scenedesmus quadricauda	ECHA Dossier			
	Acute crustacea toxicity	EC50 mg/l	>10000	48 h	Daphnia magna (24h)	ECHA Dossier	OECD Guideline 202		
78-93-3	butanone								
	Acute fish toxicity	LC50 mg/l	2993	96 h	Pimephales promelas	ECHA Dossier	OECD 203		
	Acute algae toxicity	ErC50 mg/l	1972	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	OECD 201		
	Acute crustacea toxicity	EC50	308 mg/l	48 h	Daphnia magna	ECHA Dossier	OECD 202		
3734-33-6	Denatoniumbenzoate								
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)	suppliers SDS.			
	Acute crustacea toxicity	EC50	13 mg/l	48 h	Daphnia magna (Big water flea)	suppliers SDS.			

## 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation		-			
64-17-5	ethanol					
	other guideline	84%	20	ECHA Dossier		
	Biodegradable.	•	-			
67-63-0	2-propanol					
	EU Method C.5/ EU Method C.6	53%	5	ECHA Dossier		
	Easily biodegradable (concerning to the criteria of the	e OECD)				
78-93-3	butanone					
		98%	28	ECHA Dossier		
	Readily biodegradable (according to OECD criteria).	•				

## 12.3. Bioaccumulative potential

The product has not been tested.

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,31
67-63-0	2-propanol	0,05
78-93-3	butanone	0,3



according to UK REACH Regulation

## Ethanol 96 %, denatured (MEK/IPA/BTX)

Revision date: 25.01.2024 Product code: 11470.xxxxx Page 11 of 15

### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

The product has not been tested.

#### **Further information**

Avoid release to the environment. Do not allow to enter into surface water or drains.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process. Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

### List of Wastes Code - residues/unused products

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals: laboratory chemicals, consisting of or containing hazardous substances.

including mixtures of laboratory chemicals; hazardous waste

### List of Wastes Code - used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances,

including mixtures of laboratory chemicals; hazardous waste

## List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

### Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

### **SECTION 14: Transport information**

# Land transport (ADR/RID)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION

14.3. Transport hazard class(es):314.4. Packing group:II

Hazard label: 3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L



according to UK REACH Regulation

Revision date: 25.01.2024 Product code: 11470.xxxxx Page 12 of 15

Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: 144
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: A3 A58 A180

Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. Refer to section 6-8



## **Safety Data Sheet**

according to UK REACH Regulation

## Ethanol 96 %, denatured (MEK/IPA/BTX)

Revision date: 25.01.2024 Product code: 11470.xxxxx Page 13 of 15

### 14.7. Maritime transport in bulk according to IMO instruments

No information available.

### Other applicable information

No information available.

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive

P5c FLAMMABLE LIQUIDS

2012/18/EU (SEVESO III):

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

ethanol 2-propanol butanone

## **SECTION 16: Other information**

### Changes

This data sheet contains changes from the previous version in section(s): 1,3,13,14,15.

Rev. 1,0; 16.05.2023; Recreation from collect\_SDB 11067

Rev. 1,1; 23.05.2023; general adjustment(s)



### according to UK REACH Regulation

### Ethanol 96 %, denatured (MEK/IPA/BTX)

Revision date: 25.01.2024 Product code: 11470.xxxxx Page 14 of 15

### Abbreviations and acronyms

Flam. Liq: Flammable liquids Acute Tox: Acute toxicity Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

AGW: Arbeitsplatzgrenzwert AVV: Abfallverzeichnisverordnung CAS Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European LIst of Notified Chemical Substances

ECHA: European Chemicals Agency EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level

NLP: No-Longer Polymers N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern TRGS Technische Regeln fuer Gefahrstoffe

**UN: United Nations** 

VOC: Volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrdungsklasse

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

**UN: United Nations** 

CAS: Chemical Abstracts Service DNEL: Derived No Effect Level



according to UK REACH Regulation

## Ethanol 96 %, denatured (MEK/IPA/BTX)

Product code: 11470.xxxxx Revision date: 25.01.2024 Page 15 of 15

DMFL: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules MFAG: Medical First Aid Guide

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method

### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

**EUH066** 

Repeated exposure may cause skin dryness or cracking.

### **Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according to Regulation (EC) No 1272/2008 [CLP]

- Classification procedure:

Health hazards: Calculation method. Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)