

# **Safety Data Sheet**

according to UK REACH Regulation

## Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx Page 1 of 16

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Ether - Ethanol (1:1)

UFI: NRHC-E1MV-J00Q-9XY1

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Use as laboratory reagent.

## Uses advised against

Any non-intended use.

## 1.3. Details of the supplier of the safety data sheet

Company name: MORPHISTO GmbH
Street: Schumannstr. 142/144
Place: D-63069 Offenbach

Telephone: +49 (0) 69 / 400 3019-60 Telefax: +49 (0) 69 / 400 3019-64

E-mail: info@morphisto.de Contact person: Morphisto GmbH

E-mail: gefahrstoffmanagement@morphisto.de

Internet: http://www.morphisto.de

**1.4. Emergency telephone** Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

number:

## **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Flam. Liq. 1; H224 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

## **GB CLP Regulation**

#### Hazard components for labelling

diethyl ether

Signal word: Danger

Pictograms:





## **Hazard statements**

H224 Extremely flammable liquid and vapour. H336 May cause drowsiness or dizziness.

## **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed. P261 Avoid breathing Vapour.

P312 Call a POISON CENTER/doctor if you feel unwell.

P370+P378 In case of fire: Use sand, extinguishing powder or alcohol-resistant foam to extinguish.



according to UK REACH Regulation

Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx Page 2 of 16

P403+P235 Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

EUH019 May form explosive peroxides.

EUH066 Repeated exposure may cause skin dryness or cracking.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





#### **Hazard statements**

H224

## **Precautionary statements**

P210-P233-P370+P378-P403+P235

#### 2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

## Relevant ingredients

| CAS No  | Chemical name   |              |                  | Quantity    |  |
|---------|---|--------------|------------------|-------------|--|
|         | EC No   | Index No     | REACH No         |             |  |
|         | Classification (GB CLP Regu   | lation)      | •                |             |  |
| 60-29-7 | diethyl ether   |              |                  | 50 - < 55 % |  |
|         | 200-467-2   | 603-022-00-4 | 01-2119535785-29 |             |  |
|         | Flam. Liq. 1, Acute Tox. 4, STOT SE 3; H224 H302 H336 EUH019 EUH066 |              |                  |             |  |
| 64-17-5 | Ethanol   | 45 - < 50 %  |                  |             |  |
|         | 200-578-6   | 603-002-00-5 | 01-2119457610-43 |             |  |
|         | Flam. Liq. 2, Eye Irrit. 2; H22                                     | 5 H319       |                  |             |  |
| 78-93-3 | butanone  |              |                  | < 1 %       |  |
|         | 201-159-0   | 606-002-00-3 | 01-2119457290-43 |             |  |
|         | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066        |              |                  |             |  |

Full text of H and EUH statements: see section 16.



# **Safety Data Sheet**

according to UK REACH Regulation

Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx Page 3 of 16

Specific Conc. Limits, M-factors and ATE

| CAS No  | EC No   | Chemical name   | Quantity    |  |  |  |  |
|---------|---|---|-------------|--|--|--|--|
|         | Specific Conc.                                      | Specific Conc. Limits, M-factors and ATE  |             |  |  |  |  |
| 60-29-7 | 200-467-2   | diethyl ether   | 50 - < 55 % |  |  |  |  |
|         | dermal: LD50 =                                      | dermal: LD50 = > 20000 mg/kg; oral: LD50 = 1215 mg/kg   |             |  |  |  |  |
| 64-17-5 | 200-578-6   | Ethanol   | 45 - < 50 % |  |  |  |  |
|         |   | inhalation: LC50 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg Eye Irrit. 2; H319: >= 50 - 100 |             |  |  |  |  |
| 78-93-3 | 201-159-0   | butanone  | < 1 %       |  |  |  |  |
|         | dermal: LD50 = >2000 mg/kg; oral: LD50 = 2054 mg/kg |   |             |  |  |  |  |

#### **Further Information**

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Remove contaminated, saturated clothing immediately.

#### After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). In case of accident by inhalation: remove casualty to fresh air and keep at rest. Get immediate medical advice/attention.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

## After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Get immediate medical advice/attention.

## 4.2. Most important symptoms and effects, both acute and delayed

No information available.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

#### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

In case of major fire and large quantities: Water spray jet. alcohol resistant foam.

## Unsuitable extinguishing media

High power water jet.

# 5.2. Special hazards arising from the substance or mixture

Extremely flammable liquid and vapour. Vapours can form explosive mixtures with air. In case of fire may be liberated: Carbon monoxide (CO). Carbon dioxide (CO2). Formaldehyde.

#### 5.3. Advice for firefighters



## **Safety Data Sheet**

according to UK REACH Regulation

## Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx Page 4 of 16

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

#### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. (See section 8.) Ventilate affected area. Remove persons to safety.

#### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Eliminate leaks immediately. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## 6.3. Methods and material for containment and cleaning up

#### For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### Other information

The contaminated area should be cleaned up immediately with: a concentrated aqueous sodium bisulfite solution. Rinse with water.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Technical ventilation of workplace. Wear suitable protective clothing. (See section 8.) Avoid exposure - obtain special instructions before use.

Avoid contact with skin, eyes and clothes.

# Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Flammable vapours can accumulate in head space of closed systems. Heating causes rise in pressure with risk of bursting.

# Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Take off immediately all contaminated clothing and wash it before reuse. Always close containers tightly after the removal of product. Used working clothes should not be worn outside the work area. Street clothing should be stored seperately from work clothing. Protect skin by using skin protective cream.

## Further information on handling

Flammable vapours can accumulate in head space of closed systems.

General protection and hygiene measures: refer to chapter 8



according to UK REACH Regulation

# Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx Page 5 of 16

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Recommended storage temperature: 15-25°C

## Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances or mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

## Further information on storage conditions

Keep/Store only in original container. Ensure adequate ventilation of the storage area. Store small packages in a suitable, robust cabinet.

Protect against: UV-radiation/sunlight., Heat

## 7.3. Specific end use(s)

See section 1.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### **Exposure limits (EH40)**

| CAS No  | Substance                         | ppm  | mg/m³ | fibres/ml | Category      | Origin |
|---------|-----------------------------------|------|-------|-----------|---------------|--------|
| 78-93-3 | Butan-2-one (methyl ethyl ketone) | 200  | 600   |           | TWA (8 h)     | WEL    |
|         |                                   | 300  | 899   |           | STEL (15 min) | WEL    |
| 60-29-7 | Diethyl ether                     | 100  | 310   |           | TWA (8 h)     | WEL    |
|         |                                   | 200  | 620   |           | STEL (15 min) | WEL    |
| 64-17-5 | Ethanol                           | 1000 | 1920  |           | TWA (8 h)     | WEL    |

#### **Biological Monitoring Guidance Values (EH40)**

| CAS No  | Substance   | Parameter   | Value     | Test material | Sampling time |
|---------|-------------|-------------|-----------|---------------|---------------|
| 78-93-3 | Butan-2-one | butan-2-one | 70 µmol/L | urine         | Post shift    |



according to UK REACH Regulation

Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx Page 6 of 16

# **DNEL/DMEL values**

| CAS No                   | Substance      |                |          |                      |
|--------------------------|----------------|----------------|----------|----------------------|
| DNEL type                |                | Exposure route | Effect   | Value                |
| 60-29-7                  | diethyl ether  |                |          |                      |
| Worker DNEL              | ., long-term   | inhalation     | systemic | 308 mg/m³            |
| Worker DNEL              | ., acute       | inhalation     | systemic | 616 mg/m³            |
| Worker DNEL              | ., long-term   | dermal         | systemic | 44 mg/kg bw/day      |
| Consumer DN              | NEL, long-term | inhalation     | systemic | 54.5 mg/m³           |
| Consumer DN              | NEL, long-term | dermal         | systemic | 15.6 mg/kg<br>bw/day |
| Consumer DN              | NEL, long-term | oral           | systemic | 15.6 mg/kg<br>bw/day |
| 64-17-5                  | Ethanol        |                |          |                      |
| Worker DNEL              | ., acute       | inhalation     | local    | 1900 mg/m³           |
| Worker DNEL              | ., long-term   | dermal         | systemic | 343 mg/kg bw/day     |
| Worker DNEL              | ., long-term   | inhalation     | systemic | 950 mg/m³            |
| Consumer DN              | NEL, acute     | inhalation     | local    | 950 mg/m³            |
| Consumer DN              | NEL, long-term | dermal         | systemic | 206 mg/kg bw/day     |
| Consumer DN              | NEL, long-term | inhalation     | systemic | 114 mg/m³            |
| Consumer DNEL, long-term |                | oral           | systemic | 87 mg/kg bw/day      |
| 78-93-3                  | butanone       |                |          |                      |
| Worker DNEL              | , long-term    | inhalation     | systemic | 600 mg/m³            |
| Worker DNEL              | ., long-term   | dermal         | systemic | 1161 mg/kg<br>bw/day |



according to UK REACH Regulation

# Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx Page 7 of 16

#### **PNEC values**

| CAS No                               | Substance                             |             |
|--------------------------------------|---------------------------------------|-------------|
| Environmen                           | tal compartment                       | Value       |
| 60-29-7                              | diethyl ether                         |             |
| Freshwater                           |                                       | 2 mg/l      |
| Freshwater                           | (intermittent releases)               | 1.65 mg/l   |
| Marine wate                          | or .                                  | 0.2 mg/l    |
| Freshwater                           | sediment                              | 9.14 mg/kg  |
| Marine sedi                          | ment                                  | 0.914 mg/kg |
| Micro-organ                          | isms in sewage treatment plants (STP) | 4.2 mg/l    |
| Soil                                 |                                       | 0.66 mg/kg  |
| 64-17-5                              | Ethanol                               |             |
| Freshwater                           |                                       | 0,96 mg/l   |
| Freshwater                           | (intermittent releases)               | 2,75 mg/l   |
| Marine water                         |                                       | 0,79 mg/l   |
| Marine water (intermittent releases) |                                       | 2,75 mg/l   |
| Freshwater                           | sediment                              | 3,6 mg/kg   |
| Marine sedi                          | ment                                  | 2,9 mg/kg   |
| Secondary p                          | poisoning                             | 0,72 mg/kg  |
| Micro-organ                          | isms in sewage treatment plants (STP) | 580 mg/l    |
| Soil                                 |                                       | 0,63 mg/kg  |
| 78-93-3                              | butanone                              |             |
| Freshwater                           |                                       | 55,8 mg/l   |
| Freshwater (intermittent releases)   |                                       | 55,8 mg/l   |
| Marine water                         |                                       | 55,8 mg/l   |
| Freshwater sediment                  |                                       | 284,7 mg/kg |
| Marine sediment                      |                                       | 284,7 mg/kg |
| Micro-organ                          | isms in sewage treatment plants (STP) | 709 mg/l    |
| Soil                                 |                                       | 22,5 mg/kg  |

#### 8.2. Exposure controls











Print date: 18.03.2024

## Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Technical ventilation of workplace.

# Individual protection measures, such as personal protective equipment

## Eye/face protection

Wear eye/face protection. Suitable eye protection: Tightly sealed safety glasses. EN 166

## **Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the



#### according to UK REACH Regulation

## Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx Page 8 of 16

supplier of these gloves. Wear suitable gloves. Suitable material:

Multilayer glove - PE / EVAL / PE (PE = polyethylene, EVAL = ethylene vinyl alcohol copolymer)

Breakthrough time >= 8 h

Before using check leak tightness / impermeability.

In the case of wanting to use the gloves again, clean them before taking off and air them well.

#### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing Wear fire resistant or flame retardant clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

# **Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Respiratory protection necessary at:

Insufficient ventilation.

insufficient absorbtion.

exceeding exposure limit values.

Suitable respiratory protective equipment: Protective respiration apparatus not using surrounding air (breathing apparatus) (DIN EN 133).

Details on the requirements for use and maximum concentrations can be found in the "Rules for the use of respiratory protective devices" (BGR 190).

#### Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing . .

## **Environmental exposure controls**

Do not allow uncontrolled discharge of product into the environment.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: characteristic

Melting point/freezing point:

Boiling point or initial boiling point and

34,6 °C

boiling range:

Flammability: not determined Lower explosion limits: 1.7 vol. % Upper explosion limits: 39 vol. % -40 °C Flash point: Auto-ignition temperature: not determined Decomposition temperature: not determined pH-Value: not determined Viscosity / kinematic: not determined

(at 20 °C)

Water solubility: partially miscible

(at 20 °C)

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 589,6 hPa

(at 20 °C)

Vapour pressure: 1701,7 hPa

(at 50 °C)

Density (at 20 °C): 0,75 g/cm³
Relative vapour density: not determined



## **Safety Data Sheet**

according to UK REACH Regulation

## Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx Page 9 of 16

Particle characteristics: not applicable

#### 9.2. Other information

## Information with regard to physical hazard classes

Explosive properties

May form explosive peroxides.

Oxidizing properties

none

## Other safety characteristics

Evaporation rate: not determined Solvent separation test: not determined Solid content: not determined Pour point: not determined Viscosity / dynamic: not determined

(at 40 °C)

Flow time: not determined

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Extremely flammable liquid and vapour. Explosive. No information available.

#### 10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

#### 10.3. Possibility of hazardous reactions

May form explosive peroxides.

Heating causes rise in pressure with risk of bursting.

## 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Handle with care - avoid bumps, friction and impact. Explosive. Remove all sources of ignition. Keep away from: Heat. Ignition. In case of warming: Ignition hazard.

#### 10.5. Incompatible materials

Protect against: Contact with air/oxygen. Materials to avoid: Substances which in contact with water, emit flammable gases. Organic peroxides Oxidizing agents, strong. Reducing agents, strong. Strong acid.

## 10.6. Hazardous decomposition products

May form explosive peroxides. In case of fire may be liberated: Carbon monoxide (CO). Carbon dioxide (CO2). Formaldehyde.

## **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix** calculated

ATE (oral) 2320 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



## **Safety Data Sheet**

according to UK REACH Regulation

# Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx Page 10 of 16

| CAS No  | Chemical name           | Chemical name |         |         |               |                    |
|---------|-------------------------|---------------|---------|---------|---------------|--------------------|
|         | Exposure route          | Dose          |         | Species | Source        | Method             |
| 60-29-7 | diethyl ether           |               |         |         |               |                    |
|         | oral                    | LD50<br>mg/kg | 1215    | Rat     | ECHA Dossier  | OECD Guideline 401 |
|         | dermal                  | LD50<br>mg/kg | > 20000 | Rabbit  | ECHA Dossier  | OECD Guideline 402 |
| 64-17-5 | Ethanol                 |               |         |         |               |                    |
|         | oral                    | LD50<br>mg/kg | >5000   | Rat     | ECHA Dossier  |                    |
|         | dermal                  | LD50<br>mg/kg | >2000   | Rabbit  | ECHA Dossier  |                    |
|         | inhalation (4 h) vapour | LC50<br>mg/l  | 124,7   | Rat     | ECHA Dossier  |                    |
| 78-93-3 | butanone                |               |         |         |               |                    |
|         | oral                    | LD50<br>mg/kg | 2054    | Ratte   | SDB Lieferant |                    |
|         | dermal                  | LD50<br>mg/kg | >2000   | Rabbit  | ECHA Dossier  |                    |

# Irritation and corrosivity

Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

## Sensitising effects

Based on available data, the classification criteria are not met.

# Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (diethyl ether)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

# **Aspiration hazard**

Based on available data, the classification criteria are not met.

# 11.2. Information on other hazards

# **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

## Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx

Page 11 of 16

Print date: 18.03.2024

| CAS No  | Chemical name            |               |          |           |                                      |              |          |
|---------|--------------------------|---------------|----------|-----------|--------------------------------------|--------------|----------|
|         | Aquatic toxicity         | Dose          |          | [h]   [d] | Species                              | Source       | Method   |
| 60-29-7 | diethyl ether            |               |          |           |                                      |              |          |
|         | Acute algae toxicity     | ErC50<br>mg/l | >100     | 72 h      | Desmodesmus subspicatus              | ECHA Dossier |          |
|         | Crustacea toxicity       | NOEC<br>mg/l  | >100     | 21 d      | Desmodesmus<br>subspicatus           |              |          |
| 64-17-5 | Ethanol                  |               |          |           |                                      |              |          |
|         | Acute fish toxicity      | LC50<br>mg/l  | 14200    | 96 h      | Pimephales promelas (fathead minnow) | ECHA Dossier |          |
|         | Acute algae toxicity     | ErC50         | 275 mg/l | 72 h      | Chlorella vulgaris                   | ECHA Dossier |          |
|         | Acute crustacea toxicity | EC50<br>mg/l  | 5012     |           | Ceriodaphnia dubia<br>(water flea)   | ECHA Dossier |          |
|         | Crustacea toxicity       | NOEC          | 9,6 mg/l | 9 d       | Daphnia magna                        | ECHA Dossier |          |
| 78-93-3 | butanone                 |               |          |           |                                      |              |          |
|         | Acute fish toxicity      | LC50<br>mg/l  | 2993     | 96 h      | Pimephales promelas                  | ECHA Dossier | OECD 203 |
|         | Acute algae toxicity     | ErC50<br>mg/l | 1972     | 72 h      | Pseudokirchnerella<br>subcapitata    | ECHA Dossier | OECD 201 |
|         | Acute crustacea toxicity | EC50          | 308 mg/l | 48 h      | Daphnia magna                        | ECHA Dossier | OECD 202 |

# 12.2. Persistence and degradability

The product has not been tested.

| CAS No  | Chemical name                                       |       |    |              |  |  |  |
|---------|---|-------|----|--------------|--|--|--|
|         | Method  | Value | d  | Source       |  |  |  |
|         | Evaluation  | -     | -  | •            |  |  |  |
| 64-17-5 | Ethanol   |       |    |              |  |  |  |
|         | other guideline                                     | 84%   | 20 | ECHA Dossier |  |  |  |
|         | Biodegradable.                                      |       |    |              |  |  |  |
| 78-93-3 | butanone  |       |    |              |  |  |  |
|         |   | 98%   | 28 | ECHA Dossier |  |  |  |
|         | Readily biodegradable (according to OECD criteria). |       |    |              |  |  |  |

## 12.3. Bioaccumulative potential

The product has not been tested.

## Partition coefficient n-octanol/water

| CAS No  | Chemical name | Log Pow |
|---------|---------------|---------|
| 60-29-7 | diethyl ether | 1,19    |
| 64-17-5 | Ethanol       | -0,31   |
| 78-93-3 | butanone      | 0,3     |

## **BCF**

| CAS No  | Chemical name | BCF  | Species | Source |
|---------|---------------|------|---------|--------|
| 60-29-7 | diethyl ether | 2,29 |         |        |

## 12.4. Mobility in soil

No information available.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

## 12.6. Endocrine disrupting properties



according to UK REACH Regulation

# Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx Page 12 of 16

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### **Further information**

Avoid release to the environment. Do not allow uncontrolled discharge of product into the environment.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

#### List of Wastes Code - residues/unused products

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

## List of Wastes Code - used product

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused

products; organic wastes containing hazardous substances; hazardous waste

#### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

nazaradad dabatan

# Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### **SECTION 14: Transport information**

## Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Diethyl ether, Ethanol)

14.3. Transport hazard class(es):314.4. Packing group:1Hazard label:3



Classification code: F1
Special Provisions: 274
Limited quantity: 0
Excepted quantity: E3
Transport category: 1
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Diethyl ether, Ethanol)



# **Safety Data Sheet**

according to UK REACH Regulation

# Ether - Ethanol (1:1)Revision date: 23.11.2023Product code: 15360.xxxxxPage 13 of 16

14.3. Transport hazard class(es):314.4. Packing group:IHazard label:3



Classification code: F1
Special Provisions: 274
Limited quantity: 0
Excepted quantity: E3

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993

**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (diethyl ether, ethanol)

14.3. Transport hazard class(es):314.4. Packing group:IHazard label:3



Special Provisions: 274
Limited quantity: 0
Excepted quantity: E3
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993

**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (diethyl ether, ethanol)

14.3. Transport hazard class(es):314.4. Packing group:IHazard label:3



Special Provisions: A3

Limited quantity Passenger: Forbidden Passenger LQ: Forbidden Excepted quantity: E3

IATA-packing instructions - Passenger: 351
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 361
IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. See section 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



# **Safety Data Sheet**

#### according to UK REACH Regulation

Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx Page 14 of 16

## **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial not determined

emissions:

Directive 2004/42/EC on VOC in

paints and varnishes:

not determined

Information according to Directive

P5a FLAMMABLE LIQUIDS

2012/18/EU (SEVESO III):

#### **Additional information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

#### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

#### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

diethyl ether Ethanol butanone

## **SECTION 16: Other information**

## Changes

This data sheet contains changes from the previous version in section(s):

1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

Rev. 2,0; 23.11.2023, Individual safety data sheet based on 15360\_collect



## **Safety Data Sheet**

#### according to UK REACH Regulation

# Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx Page 15 of 16

## Abbreviations and acronyms

Flam. Liq: Flammable liquids Acute Tox: Acute toxicity Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

CAS Chemical Abstracts Service DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level

NTP: National Toxicology Program

N/A: not applicable

OSHA: Occupational Safety and Health Administration

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail )

SARA: Superfund Amendments and Reauthorization Act

SVHC: substance of very high concern TRGS Technische Regeln fuerGefahrstoffe TSCA: Toxic Substances Control Act VOC: Volatile Organic Compounds

voc: volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrdungsklasse

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

**UN: United Nations** 

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)



## **Safety Data Sheet**

according to UK REACH Regulation

Ether - Ethanol (1:1)

Revision date: 23.11.2023 Product code: 15360.xxxxx Page 16 of 16

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules MFAG: Medical First Aid Guide

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety

assessment, chapter R.20 (Table of terms and abbreviations). EC/EEC: European Community/European Economic Community

EU: European Union M-factor: Multiplying factor

IATA: International Air Transport Association

DGR: Dangerous Goods Regulations

ICAO: International Civil Aviation Organization

TI: Technical Instructions VOC: volatile organic compound

Classification for mixtures and used evaluation method according to GB CLP Regulation

| Classification     | Classification procedure |
|--------------------|--------------------------|
| Flam. Liq. 1; H224 | On basis of test data    |
| STOT SE 3; H336    | Calculation method       |

#### Relevant H and EUH statements (number and full text)

H224 Extremely flammable liquid and vapour.
H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

EUH019 May form explosive peroxides.
EUH066 Repeated exposure may cause skin dryness or cracking.

## **Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according EC regulation 1272/2008 (CLP): - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)