according to UK REACH Regulation

# Martius Yellow 0.5 %

Revision date: 11.08.2023

Product code: 11457.xxxxx

Page 1 of 16

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Martius Yellow 0.5 %

UFI:

5NQ0-Y1PG-4006-GJK7

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Use as laboratory reagent.Intended for scientific research and development.

### Uses advised against

Any non-intended use.

# 1.3. Details of the supplier of the safety data sheet

MORPHISTO GmbH	
Schumannstr. 142/144	
D-63069 Offenbach	
+49 (0) 69 / 400 3019-60	Telefax: +49 (0) 69 / 400 3019-64
info@morphisto.de	
Morphisto GmbH	
gefahrstoffmanagement@morphisto.de	
http://www.morphisto.de	
Poison Information Center Mainz, Germany, T	el: +49(0)6131/19240
	Schumannstr. 142/144 D-63069 Offenbach +49 (0) 69 / 400 3019-60 info@morphisto.de Morphisto GmbH gefahrstoffmanagement@morphisto.de http://www.morphisto.de

### number:

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

#### **GB CLP Regulation**

Flam. Liq. 2; H225 Skin Irrit. 2; H315 Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

GB	CLP	Regulation
----	-----	------------

Signal word:	Danger
	Dungoi

Pictograms:



#### Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P282	Wear cold insulating gloves and either face shield or eye protection.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use sand, extinguishing powder or alcohol-resistant foam to extinguish.

### according to UK REACH Regulation

# Martius Yellow 0.5 %

Revision date: 11.08.2023

Product code: 11457.xxxxx

Page 2 of 16

### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger Pictograms:



#### 2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1% or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more have endocrine disrupting properties.

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

#### **Relevant ingredients**

CAS No	Chemical name	Chemical name		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation	)	-	
64-17-5	Ethanol			95 - < 100 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H31	•		
12501-23-4	Phosphotungstic acid			1 - < 5 %
	215-682-7			
	Acute Tox. 4, Skin Corr. 1C, Eye I	Dam. 1, Aquatic Chronic 2; H302 H3	14 H318 H411	
78-93-3	butanone	butanone		
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
64-17-5	200-578-6	Ethanol	95 - < 100 %
		i0 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 t. 2; H319: >= 50 - 100	
12501-23-4	215-682-7	Phosphotungstic acid	1 - < 5 %
	oral: LD50 = 20	000 mg/kg	
78-93-3	201-159-0	butanone	< 1 %
	dermal: LD50 :	= >2000 mg/kg; oral: LD50 = 2054 mg/kg	

### **Further Information**

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

## **SECTION 4: First aid measures**

according to UK REACH Regulation

# Martius Yellow 0.5 %

Revision date: 11.08.2023

Product code: 11457.xxxxx

Page 3 of 16

### 4.1. Description of first aid measures

### **General information**

Remove affected person from the danger area and lay down. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### After inhalation

Provide fresh air. If unconscious but breathing normally, place in recovery position and seek medical advice. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Seek medical advice.

### 4.2. Most important symptoms and effects, both acute and delayed

Acute effects: Mucous membrane irritation after eye contact or inhalation. Delayed effects: Impairment of inhibitory functions of the central nervous system, skin redness, nausea after ingestion of large amounts.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder

#### Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air. The formation of combustible vapours is possible at temperatures above: 7°C.Vapours are heavier than air and will spread at floor level. In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2).

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. In case of fire and/or explosion do not breathe fumes.

### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

## General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Take action to prevent static discharges. Ventilate affected area. Special danger of slipping by leaking/spilling product.

according to UK REACH Regulation

# Martius Yellow 0.5 %

Revision date: 11.08.2023

Product code: 11457.xxxxx

Page 4 of 16

### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

#### For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal. Clear contaminated areas thoroughly.

## 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment. (See section 8.) Use extractor hood (laboratory).

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Flammable vapours can accumulate in head space of closed systems. Heating causes rise in pressure with risk of bursting.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product.

#### Further information on handling

General protection and hygiene measures: refer to chapter 8

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep/Store only in original container. Protect from direct sunlight.

Ensure adequate ventilation of the storage area. Concentrated vapours are heavier than air.

Suitable material for Container: Stainless steel. (1.4301 (V2), 1.4401 (V4)); iron. solvent resistant plastics. Unsuitable materials for Container: Aluminium. Rubber, various plastics.

#### Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances or mixtures which, in contact with water, emit flammable gases. Oxidizing liquids.ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

#### Further information on storage conditions

Recommended storage temperature: 15-25 °C

Protect against: UV-radiation/sunlight. heat. Cold.



## according to UK REACH Regulation

# Martius Yellow 0.5 %

Revision date: 11.08.2023

Product code: 11457.xxxxx

Page 5 of 16

# 7.3. Specific end use(s)

See section 1.

# SECTION 8: Exposure controls/personal protection

# 8.1. Control parameters

### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

## **Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

### **DNEL/DMEL** values

CAS No	Substance				
DNEL type	DNEL type Exposure route Effect Value				
64-17-5	Ethanol				
Worker DNE	L, acute	inhalation	local	1900 mg/m³	
Worker DNE	L, long-term	dermal	systemic	343 mg/kg bw/day	
Worker DNE	L, long-term	inhalation	systemic	950 mg/m³	
Consumer D	NEL, acute	inhalation	local	950 mg/m³	
Consumer D	NEL, long-term	dermal	systemic	206 mg/kg bw/day	
Consumer D	NEL, long-term	inhalation	systemic	114 mg/m³	
Consumer D	NEL, long-term	oral	systemic	87 mg/kg bw/day	
78-93-3	butanone				
Worker DNE	L, long-term	inhalation	systemic	600 mg/m³	
Worker DNE	L, long-term	dermal	systemic	1161 mg/kg bw/day	



according to UK REACH Regulation

# Martius Yellow 0.5 %

Revision date: 11.08.2023

Product code: 11457.xxxxx

Page 6 of 16

#### **PNEC** values

CAS No	Substance	
Environmen	tal compartment	Value
64-17-5	Ethanol	
Freshwater		0,96 mg/l
Freshwater	(intermittent releases)	2,75 mg/l
Marine wate	r	0,79 mg/l
Marine wate	r (intermittent releases)	2,75 mg/l
Freshwater	sediment	3,6 mg/kg
Marine sedir	ment	2,9 mg/kg
Secondary p	poisoning	0,72 mg/kg
Micro-organ	isms in sewage treatment plants (STP)	580 mg/l
Soil		0,63 mg/kg
78-93-3	butanone	
Freshwater		55,8 mg/l
Freshwater	(intermittent releases)	55,8 mg/l
Marine wate	r	55,8 mg/l
Freshwater sediment		284,7 mg/kg
Marine sediment		284,7 mg/kg
Micro-organ	isms in sewage treatment plants (STP)	709 mg/l
Soil		22,5 mg/kg

### 8.2. Exposure controls









### Appropriate engineering controls

Provide adequate ventilation.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Use extractor hood (laboratory).

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Suitable eye protection: goggles. Tightly sealed safety glasses. EN 166

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. In case of prolonged or frequently repeated skin contact:

Tested protective gloves are to be worn:

### Suitable material:

Butyl rubber. (0,7 mm, Breakthrough time >=480 min, penetration time (maximum wearing period): 160 min): NBR (Nitrile rubber). (0,4 mm, Breakthrough time >=120 min, penetration time (maximum wearing period): 40 min)

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.



according to UK REACH Regulation

## Martius Yellow 0.5 %

Revision date: 11.08.2023

Product code: 11457.xxxxx

Page 7 of 16

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

### Skin protection

Protective clothing. (fire retardant.)

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

### **Respiratory protection**

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Insufficient ventilation.

exceeding exposure limit values

generation/formation of aerosols

Suitable respiratory protective equipment:

gas filtering equipment (EN 141). Type : a

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

The wearing time limitations according to GefStoffV in conjunction with the rules for the use of respiratory protective devices (BGR 190) must be observed.

#### **Thermal hazards**

Flame-retardant protective clothing. Wear anti-static footwear and clothing .

### Environmental exposure controls

Do not allow to enter into surface water or drains.

#### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	orange	
Odour:	alkoholisch	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and		78 °C
boiling range:		
Flammability:		not determined
Lower explosion limits:		3,1 vol. %
Upper explosion limits:		27,7 vol. %
Flash point:		12 °C
Auto-ignition temperature:		400 °C
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:		completely miscible
(at 20 °C)		
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		58 hPa
(at 20 °C)		
Vapour pressure:		293 hPa
(at 50 °C)		0.01 m/am3
Density (at 20 °C):		0,81 g/cm <sup>3</sup> not determined
Relative vapour density:		not determined

### according to UK REACH Regulation

	Martius Yellow 0.5 %	
Revision date: 11.08.2023	Product code: 11457.xxxxx	Page 8 of 16
Particle characteristics:	not applicable	
9.2. Other information		
Information with regard to physical hazard clase Explosive properties	ises	
	nmable solvents can accumulate in the gas phase of herefore keep away from fire and sources of ignition.	
Self-ignition temperature		
Gas:	not determined	
Oxidizing properties		
none		
Other safety characteristics		
Evaporation rate:	not determined	
Solvent separation test:	not determined	
Solvent content:	not determined	
Solid content:	not determined	
Sublimation point:	not determined	
Softening point:	not determined	
Pour point:	not determined	
Viscosity / dynamic:	not determined	

not determined

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Flow time:

Highly flammable. No information available.

#### 10.2. Chemical stability

Stable under normal storage and handling conditions.

#### 10.3. Possibility of hazardous reactions

Explosion risk in contact with: Oxidizing agents, strong. nitric acid. Hydrogenium peroxide. Exothermic reactions with: Alkali metals. Alkaline earth metals. Reducing agents, strong.

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Keep away from heat. Protect from direct sunlight. Protect from moisture. In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting. Recommended storage temperature: < 40 °C

### 10.5. Incompatible materials

Materials to avoid: Substances that form flammable gases when in contact with water. Organic peroxides. Inflammatory substances. Alkali metals. Acid chlorides. Organic peroxides. Oxidizing agents.

### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2).

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Based on available data, the classification criteria are not met.

### ATEmix calculated

ATE (oral) 20325 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



### according to UK REACH Regulation

# Martius Yellow 0.5 %

Revision date: 11.08.2023

Product code: 11457.xxxxx

Page 9 of 16

CAS No	S No Chemical name					
	Exposure route	Dose		Species	Source	Method
64-17-5	Ethanol					
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier	
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier	
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	ECHA Dossier	
12501-23-4	Phosphotungstic acid					
	oral	LD50 mg/kg	2000	Ratte, weiblich	suppliers SDS.	
78-93-3	butanone					
	oral	LD50 mg/kg	2054	Ratte	SDB Lieferant	
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier	

#### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

## Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

## Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Depending on the ingested quantity the following symptoms can be induced: a reduction of inhibitions, euphoria but also dysphoria, aggressiveness, impaired motoric skills, impaired responsiveness, blurred vision and fatigue.

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Based on available data, the classification criteria are not met.



## according to UK REACH Regulation

## Martius Yellow 0.5 %

Revision date: 11.08.2023

Product code: 11457.xxxxx

Page 10 of 16

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
64-17-5	Ethanol							
	Acute fish toxicity	LC50 mg/l	14200	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier		
	Acute algae toxicity	ErC50	275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier		
	Acute crustacea toxicity	EC50 mg/l	5012	48 h	Ceriodaphnia dubia (water flea)	ECHA Dossier		
	Crustacea toxicity	NOEC	9,6 mg/l	9 d	Daphnia magna	ECHA Dossier		
12501-23-4	Phosphotungstic acid							
	Acute algae toxicity	ErC50	7,8 mg/l	72 h	Pseudokirchneriella subcapitata (Gru? nalge)		statischer Test ErC50	
	Acute crustacea toxicity	EC50 mg/l	70,8	48 h	Daphnia magna (Großer Wasserfloh)		statischer Test EC50	
	Acute bacteria toxicity	EC50 mg/l()	1000	3 h	Belebtschlamm		statischer Test ErC50	
78-93-3	butanone							
	Acute fish toxicity	LC50 mg/l	2993	96 h	Pimephales promelas	ECHA Dossier	OECD 203	
	Acute algae toxicity	ErC50 mg/l	1972	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	OECD 201	
	Acute crustacea toxicity	EC50	308 mg/l	48 h	Daphnia magna	ECHA Dossier	OECD 202	

## 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64-17-5	Ethanol			
	other guideline	84%	20	ECHA Dossier
	Biodegradable.			
78-93-3	butanone			
		98%	28	ECHA Dossier
	Readily biodegradable (according to OECD criteria).			

### 12.3. Bioaccumulative potential

The product has not been tested.

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	Ethanol	-0,31
78-93-3	butanone	0,3

### 12.4. Mobility in soil

The product has not been tested.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# 12.7. Other adverse effects



according to UK REACH Regulation

# Martius Yellow 0.5 %

Revision date: 11.08.2023

Product code: 11457.xxxxx

Page 11 of 16

No information available.

### Further information

Avoid release to the environment. Do not allow to enter into surface water or drains.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

#### List of Wastes Code - residues/unused products

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

#### List of Wastes Code - used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

#### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

#### Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.Non-contaminated packages may be recycled.

#### **SECTION 14: Transport information**

Land transport (ADR/RID)	
14.1. UN number or ID number:	UN 1170
14.2. UN proper shipping name:	ETHANOL
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
	<u>*</u>
Classification code:	F1
Special Provisions:	144 601
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1170
14.2. UN proper shipping name:	ETHANOL
14.3. Transport hazard class(es):	3
14.4. Packing group:	II



according to UK REACH Regulation

Revision date: 11.08.2023	Martius Ye Product code	llow 0.5 % e: 11457.xxxxx	Page 12 of 16
Hazard label:	3		
Classification code:	F1		
Special Provisions:	144 601 1 L		
Limited quantity: Excepted quantity:	E2		
Marine transport (IMDG)			
14.1. UN number or ID number:	UN 1170		
14.2. UN proper shipping name:	ETHANOL		
14.3. Transport hazard class(es):	3		
14.4. Packing group:	11		
Hazard label:	3		
Special Provisions:	144		
Limited quantity:	1 L		
Excepted quantity:	E2		
EmS:	F-E, S-D		
Air transport (ICAO-TI/IATA-DGR) <u>14.1. UN number or ID number:</u>	UN 1170		
14.2. UN proper shipping name:	ETHANOL		
14.3. Transport hazard class(es):	3		
14.4. Packing group:	II		
Hazard label:	3		
Special Provisions:	A3 A58 A180		
Limited quantity Passenger: Passenger LQ:	1 L Y341		
Excepted quantity:	E2		
IATA-packing instructions - Passenger:		353	
IATA-max. quantity - Passenger:		5 L	
IATA-packing instructions - Cargo:		364	
IATA-max. quantity - Cargo:		60 L	
14.5. Environmental hazards			
ENVIRONMENTALLY HAZARDOUS:	No		
14.6. Special precautions for user Warning: Combustible liquid. Refer to s			
14.7. Maritime transport in bulk according to not relevant	Divic Instruments		
SECTION 15: Regulatory information			

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# EU regulatory information

according to UK REACH Regulation

	Martius Yellow 0.5 %	
Revision date: 11.08.2023	Product code: 11457.xxxxx	Page 13 of 16
Restrictions on use (REACH, annex XVII): Entry 3, Entry 40, Entry 75		
Directive 2010/75/EU on industrial emissions:	97,04 % (786,024 g/l)	
Directive 2004/42/EC on VOC in paints and varnishes:	97,04 % (786,024 g/l)	
Information according to Directive 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS	
Additional information		
The mixture is classified as hazardous REACH 1907/2006 Appendix XVII, No	according to regulation (EC) No 1272/2008 [CLP]. (mixture): 3, 40	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juve work protection guideline' (94/33/EC).	enile
Water hazard class (D):	1 - slightly hazardous to water	
Additional information		
15.2. Chemical safety assessment		
For the following substances of this mi Ethanol	xture a chemical safety assessment has been carried out:	

butanone

# **SECTION 16: Other information**

# Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,11,12,13,14,15,16.

Rev. 1,00; 05.11.2012 Initial release

Rev. 1,1; 27.11.2019 Fusion into Collect Data SDB

Rev. 1,2; 19.06.2020, Revision Kap.1 - 16

Rev. 1,3; 11.11.2020, Adding an article Kap. 1

Rev. 2,0; 11.08.2023; general adjustment(s), Change of classification/labeling



according to UK REACH Regulation

# Martius Yellow 0.5 %

Revision date: 11.08.2023

Abbreviations and acronyms

Product code: 11457.xxxxx

Page 14 of 16

### Flam. Lig: Flammable liquids Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation STOT SE: Specific target organ toxicity - single exposure Aquatic Chronic: Chronic aquatic hazard ADR: Accord européen sur le transport des marchandises dangereuses par Route AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen AGW: Arbeitsplatzgrenzwert AVV: Abfallverzeichnisverordnung CAS Chemical Abstracts Service CLP: Classification, Labelling and Packaging of substances and mixtures DNEL: Derived No Effect Level d: dav(s) EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances ECHA: European Chemicals Agency EWC: European Waste Catalogue IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany) h: hour I OAFL: Lowest observed adverse effect level LOAEC: Lowest observed adverse effect concentration LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level NLP: No-Longer Polymers N/A: not applicable OECD: Organisation for Economic Co-operation and Development PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) REACH: Registration, Evaluation, Authorisation of Chemicals SVHC: substance of very high concern TRGS Technische Regeln fuer Gefahrstoffe UN: United Nations VOC: Volatile Organic Compounds VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe WGK: Wassergefaehrdungsklasse CLP: Classification, labelling and Packaging REACH: Registration, Evaluation and Authorization of Chemicals GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals **UN: United Nations**



according to UK REACH Regulation

# Martius Yellow 0.5 %

Revision date: 11.08.2023

Product code: 11457.xxxx

Page 15 of 16

DNFL: Derived No Effect Level DMEL: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50% EC50: Effective Concentration 50% ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration BCF: Bio-concentration factor PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Regulations concerning the international carriage of dangerous goods by rail ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) EmS: Emergency Schedules MFAG: Medical First Aid Guide MARPOL: International Convention for the Prevention of Marine Pollution from Ships IBC: Intermediate Bulk Container For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure	
Flam. Liq. 2; H225	On basis of test data	
Skin Irrit. 2; H315	Calculation method	
Eye Irrit. 2; H319	Calculation method	

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### **Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according to Regulation (EC) No 1272/2008 [CLP]

- Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



according to UK REACH Regulation

# Martius Yellow 0.5 %

Revision date: 11.08.2023

Product code: 11457.xxxxx

Page 16 of 16

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)