

according to UK REACH Regulation

Rhodamine 0,5 % in isopropanol

Revision date: 27.02.2024 Product code: 12378.xxxxx Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Rhodamine 0,5 % in isopropanol

UFI: CQ83-41D3-600Y-RY8N

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Use as laboratory reagent. Intended for scientific research and development.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: MORPHISTO GmbH
Street: Schumannstr. 142/144
Place: D-63069 Offenbach

Telephone: +49 (0) 69 / 400 3019-60 Telefax: +49 (0) 69 / 400 3019-64

E-mail: info@morphisto.de
Contact person: Morphisto GmbH

E-mail: gefahrstoffmanagement@morphisto.de

Internet: http://www.morphisto.de

1.4. Emergency telephone Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

2-propanol

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed. P261 Avoid breathing Vapour.



according to UK REACH Regulation

Rhodamine 0,5 % in isopropanol

Revision date: 27.02.2024 Product code: 12378.xxxxx Page 2 of 14

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P312 Call a POISON CENTER/doctor if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1% or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more have endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No Index No REACH No			
	Classification (GB CLP Regulation)			
67-63-0	2-propanol			95 - < 100 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits. M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. L	Specific Conc. Limits, M-factors and ATE		
67-63-0	200-661-7 2-propanol		95 - < 100 %	
	dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg			

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

First aider: Pay attention to self-protection!

After inhalation

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Provide fresh air. Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

Print date: 27.02.2024



Safety Data Sheet

according to UK REACH Regulation

Rhodamine 0,5 % in isopropanol

Revision date: 27.02.2024 Product code: 12378.xxxxx Page 3 of 14

After contact with skin

Take off contaminated clothing and wash it before reuse. Wash with plenty of water. In case of skin irritation, seek medical treatment.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air. In case of fire may be liberated: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO2).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. (See section 8.) Remove persons to safety.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Ventilate affected area.

Print date: 27.02.2024



Safety Data Sheet

according to UK REACH Regulation

Rhodamine 0,5 % in isopropanol

Revision date: 27.02.2024 Product code: 12378.xxxxx Page 4 of 14

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation as well as local exhaustion at critical locations. Avoid contact with skin, eves and clothes.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Flammable vapours can accumulate in head space of closed systems. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Take off contaminated clothing and wash it before reuse. The usual precautions for handling chemicals should be considered. Always close containers tightly after the removal of product. Protect skin by using skin protective cream.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from direct sunlight. Ensure adequate ventilation of the storage area. Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances or mixtures which, in contact with water, emit flammable gases. Oxidizing solids. ammonium nitrate. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity.

Protect against: UV-radiation/sunlight. heat. Humidity frost.

storage temperature: 15-25°C

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to UK REACH Regulation

Rhodamine 0,5 % in isopropanol

Revision date: 27.02.2024 Product code: 12378.xxxxx Page 5 of 14

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
67-63-0	2-propanol				
Worker DNEL, long-term		inhalation	systemic	500 mg/m³	
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³	
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day	
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day	
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day	

PNEC values

CAS No	Substance		
Environmental compartment Value			
67-63-0	2-propanol		
Freshwater 140,9 mg		140,9 mg/l	
Marine water		140,9 mg/l	
Freshwater sediment		552 mg/kg	
Marine sediment		552 mg/kg	
Secondary poisoning		160 mg/kg	
Soil		28 mg/kg	

8.2. Exposure controls











Print date: 27.02.2024

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles. Wear eye/face protection. Recommended eye protection brand: Tightly sealed safety glasses. (EN 166)

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Wear suitable gloves.

Suitable material:

FKM (fluororubber). - Thickness of glove material: 0,4 mm

Breakthrough time >= 8 h

Butyl rubber. - Thickness of glove material: 0,5 mm



according to UK REACH Regulation

Rhodamine 0,5 % in isopropanol

Revision date: 27.02.2024 Product code: 12378.xxxxx Page 6 of 14

Breakthrough time >= 8 h

CR (polychloroprenes, Chloroprene rubber). - Thickness of glove material: 0,5 mm

Breakthrough time >= 4 h

NBR (Nitrile rubber). - Thickness of glove material: 0,35 mm

Breakthrough time >= 8 h

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard

EN 374 derived from it.

Before using check leak tightness / impermeability.

Skin protection

Wear fire resistant or flame retardant clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

In case of inadequate ventilation wear respiratory protection. In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

exceeding exposure limit values

Insufficient ventilation.

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: A/P1-3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. The wearing time limitations according to GefStoffV in conjunction with the rules for the use of respiratory protective devices (BGR 190) must be observed.

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid. Colour: red

Odour: characteristic

Melting point/freezing point:

-88 °C

Boiling point or initial boiling point and

82 °C

boiling range:

Flammability: not applicable Lower explosion limits: 2 vol. % Upper explosion limits: 13.4 vol. % Flash point: 12 °C Auto-ignition temperature: 425 °C Decomposition temperature: not determined pH-Value: not determined Viscosity / kinematic: not determined

(at 20 °C)

Water solubility: miscible.

(at 20 °C)

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined



according to UK REACH Regulation

Rhodamine 0,5 % in isopropanol

Revision date: 27.02.2024 Product code: 12378.xxxxx Page 7 of 14

Vapour pressure: 42 hPa

(at 20 °C)

Density (at 20 °C): 0,79 g/cm³
Relative vapour density: not determined
Particle characteristics: not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties

none.

Other safety characteristics

Evaporation rate:

Solvent separation test:

not determined

Solvent content:

not determined

not determined

viscosity / dynamic:

not determined

not determined

(at 40 °C)

Flow time: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable

10.2. Chemical stability

Ignition hazard.

10.3. Possibility of hazardous reactions

see section 10.5

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong. Strong acid. strong alkalis.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



according to UK REACH Regulation

Rhodamine 0,5 % in isopropanol

Revision date: 27.02.2024 Product code: 12378.xxxxx Page 8 of 14

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
67-63-0	2-propanol					
	l - · - · ·	LD50 >5000 mg/kg	Rat	ECHA Dossier		
	dermal	LD50 >5000 mg/kg	Rabbit	ECHA Dossier		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (2-propanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain any substance that has endocrine disrupting properties in humans as no ingredient meets the criteria.

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Chemical name					
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
67-63-0	2-propanol						
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas	ECHA Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	1800		Scenedesmus quadricauda	ECHA Dossier	
	Acute crustacea toxicity	EC50 mg/l	>10000	48 h	Daphnia magna (24h)	ECHA Dossier	OECD Guideline 202

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation	-	-	•	
67-63-0	2-propanol				
	EU Method C.5/ EU Method C.6	53%	5	ECHA Dossier	
	Easily biodegradable (concerning to the criteria of the OECD)				



according to UK REACH Regulation

Rhodamine 0.5 % in isopropanol

Revision date: 27.02.2024 Product code: 12378.xxxxx Page 9 of 14

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	2-propanol	0,05

12.4. Mobility in soil

There is no data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

There is no data available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - used product

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:UN 121914.2. UN proper shipping name:ISOPROPANOL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



according to UK REACH Regulation

Rhodamine 0,5 % in isopropanol

Revision date: 27.02.2024 Product code: 12378.xxxxx Page 10 of 14



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:UN 121914.2. UN proper shipping name:ISOPROPANOL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1219 **14.2. UN proper shipping name:** ISOPROPANOL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity:

Excepted quantity:

E2

EmS:

F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:UN 121914.2. UN proper shipping name:ISOPROPANOL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity Passenger:

1 L

Passenger LQ:

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger: 353 IATA-max. quantity - Passenger: 5 L



according to UK REACH Regulation

Rhodamine 0,5 % in isopropanol

Revision date: 27.02.2024 Product code: 12378.xxxxx Page 11 of 14

IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. See section 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial not determined

emissions:

Directive 2004/42/EC on VOC in not determined

paints and varnishes:

Information according to Directive P5c F

2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

2-propanol

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,4,5,6,7,8,9,10,11,12,13,14,15,16.

Rev. 2,0: 27.02.2024; Individual safety data sheet based on 12378_collect



according to UK REACH Regulation

Rhodamine 0,5 % in isopropanol

Revision date: 27.02.2024 Product code: 12378.xxxxx Page 12 of 14

Abbreviations and acronyms

Flam. Liq: Flammable liquids

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

AGW: Arbeitsplatzgrenzwert AVV: Abfallverzeichnisverordnung CAS Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European LIst of Notified Chemical Substances

ECHA: European Chemicals Agency EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level

NLP: No-Longer Polymers

N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern TRGS Technische Regeln fuer Gefahrstoffe

UN: United Nations

VOC: Volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrdungsklasse

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LL50: Lethal loading, 50%



according to UK REACH Regulation

Rhodamine 0,5 % in isopropanol

Revision date: 27.02.2024 Product code: 12378.xxxxx Page 13 of 14

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules MFAG: Medical First Aid Guide

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety

assessment, chapter R.20 (Table of terms and abbreviations). EC/EEC: European Community/European Economic Community

EU: European Union M-factor: Multiplying factor

IATA: International Air Transport Association

DGR: Dangerous Goods Regulations

ICAO: International Civil Aviation Organization

TI: Technical Instructions VOC: volatile organic compound

Classification for mixtures and used evaluation method according to GB CLP Regulation

<u> </u>				
Classification	Classification procedure			
Flam. Liq. 2; H225	On basis of test data			
Eye Irrit. 2; H319	Calculation method			
STOT SE 3; H336	Calculation method			

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



Print date: 27.02.2024



Safety Data Sheet

according to UK REACH Regulation

Rhodamine 0,5 % in isopropanol

Revision date: 27.02.2024 Product code: 12378.xxxxx Page 14 of 14

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)