

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 1 of 18

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

UFI:

WFYE-U1E0-Q007-Q1WX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

laboratory reagent

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	MORPHISTO GmbH	
Street:	Schumannstr. 142/144	
Place:	D-63069 Offenbach	
Telephone:	+49 (0) 69 / 400 3019-60	Telefax: +49 (0) 69 / 400 3019-64
E-mail:	info@morphisto.de	
Contact person:	Morphisto GmbH	
E-mail:	gefahrstoffmanagement@morphisto.de	9
Internet:	http://www.morphisto.de	
1.4. Emergency telephone	Poison Information Center Mainz, Gern	nany, Tel: +49(0)6131/19240

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Lig. 2; H225 Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Signal word:

Pictograms:



Hazard statements

H225	
H319	

Highly flammable liquid and vapour. Causes serious eye irritation.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P337+P313	If eye irritation persists: Get medical advice/attention.
Labelling of packages	where the contents do not exceed 125 ml
Signal word:	Danger



according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxx

Page 2 of 18

Pictograms:



2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regula	ation)		
64-17-5	ethanol			60 - < 65 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225	H319		
67-63-0	2-propanol			< 1 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT			
78-93-3	butanone			< 1 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
3734-33-6	Denatoniumbenzoate			< 1 %
	223-095-2			
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H332 H302 H315 H318 H412			
7647-01-0	hydrochloric acid %			< 1 %
	231-595-7	017-002-01-X	01-2119484862-27	
	Met. Corr. 1, Skin Corr. 1B, Eye Dam. 1, STOT SE 3; H290 H314 H318 H335			

Full text of H and EUH statements: see section 16.

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 3 of 18

Specific Conc	. Limits, M-fac	tors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc	Limits, M-factors and ATE	
64-17-5	200-578-6	ethanol	60 - < 65 %
		250 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 rit. 2; H319: >= 50 - 100	
67-63-0	200-661-7	2-propanol	< 1 %
	dermal: LD50) = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
78-93-3	201-159-0	butanone	< 1 %
	dermal: LD50) = >2000 mg/kg; oral: LD50 = 2054 mg/kg	
3734-33-6	223-095-2	Denatoniumbenzoate	< 1 %
		E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = oral: ATE = 500 mg/kg	
7647-01-0	231-595-7	hydrochloric acid %	< 1 %
		2222 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 319: >= 10 - < 25 STOT SE 3; H335: >= 10 - 100	

Further Information

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. In case of accident by inhalation: remove casualty to fresh air and keep at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. In case of skin irritation, seek medical treatment.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Acute effects: Mucous membrane irritation after eye contact or inhalation. Delayed effects: Impairment of inhibitory functions of the central nervous system, skin redness, nausea after ingestion of large amounts.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Percutaneously absorbed and inhaled substance causes next to irritation of affected mucous membranes only an indicated impairment of the inhibitory functions of the central nervous system, clinically recognizable as the beginning of a euphoric stage. At the same time face and skin redness is caused by dilation of peripheral blood vessels in the body.

SECTION 5: Firefighting measures



according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 4 of 18

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air. Vapours are heavier than air and will spread at floor level.

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Hydrogen chloride (HCI).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Ventilate affected area. Special danger of slipping by leaking/spilling product.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Ventilate affected area. Clear contaminated areas thoroughly.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment. (See section 8.) Use extractor hood (laboratory).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Flammable vapours can accumulate in head space of closed systems. Heating causes rise in pressure with risk of bursting.



according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 5 of 18

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product.

Further information on handling

General protection and hygiene measures: refer to chapter 8

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep/Store only in original container. Protect from direct sunlight.

Ensure adequate ventilation of the storage area. Concentrated vapours are heavier than air. Suitable material for Container: Stainless steel. (1.4301 (V2), 1.4401 (V4)); iron. solvent resistant plastics. Unsuitable materials for Container: Aluminium. Rubber. various plastics.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances or mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Recommended storage temperature: 15-25 °C Protect against: UV-radiation/sunlight. heat. Cold. Store small packages in a suitable, robust cabinet.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
7647-01-0	Hydrogen chloride (gas and aerosol mists)	1	2		TWA (8 h)	WEL
		5	8		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift



according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 6 of 18

DNEL/DMEL values

CAS No	Substance				
DNEL type Exposure route E			Effect	Value	
64-17-5	ethanol		·		
Worker DNEL	., acute	inhalation	local	1900 mg/m³	
Worker DNEL	., long-term	dermal	systemic	343 mg/kg bw/day	
Worker DNEL	., long-term	inhalation	systemic	950 mg/m³	
Consumer DN	NEL, acute	inhalation	local	950 mg/m³	
Consumer DN	IEL, long-term	dermal	systemic	206 mg/kg bw/day	
Consumer D	NEL, long-term	inhalation	systemic	114 mg/m³	
Consumer D	NEL, long-term	oral	systemic	87 mg/kg bw/day	
67-63-0	2-propanol				
Worker DNEL	., long-term	inhalation	systemic	500 mg/m³	
Consumer DN	IEL, long-term	inhalation	systemic	89 mg/m³	
Worker DNEL	., long-term	dermal	systemic	888 mg/kg bw/day	
Consumer DN	IEL, long-term	oral	systemic	26 mg/kg bw/day	
Consumer DN	IEL, long-term	dermal	systemic	319 mg/kg bw/day	
78-93-3	butanone		·		
Worker DNEL	, long-term	inhalation	systemic	600 mg/m³	
Worker DNEL	., long-term	dermal	systemic	1161 mg/kg bw/day	
7647-01-0	hydrochloric acid %				
Worker DNEL	., acute	inhalation	local	15 mg/m³	
Worker DNEL	., long-term	inhalation	local	8 mg/m³	

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 7 of 18

PNEC values

CAS No	Substance	
Environmenta	al compartment	Value
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (i	ntermittent releases)	2,75 mg/l
Marine water		0,79 mg/l
Marine water	(intermittent releases)	2,75 mg/l
Freshwater s	ediment	3,6 mg/kg
Marine sedim	nent	2,9 mg/kg
Secondary po	pisoning	0,72 mg/kg
Micro-organis	sms in sewage treatment plants (STP)	580 mg/l
Soil		0,63 mg/kg
67-63-0	2-propanol	
Freshwater		140,9 mg/l
Marine water		140,9 mg/l
Freshwater s	ediment	552 mg/kg
Marine sedim	nent	552 mg/kg
Secondary po	pisoning	160 mg/kg
Soil		28 mg/kg
78-93-3	butanone	
Freshwater		55,8 mg/l
Freshwater (i	ntermittent releases)	55,8 mg/l
Marine water		55,8 mg/l
Freshwater sediment		284,7 mg/kg
Marine sediment 284,7 m		284,7 mg/kg
Micro-organis	sms in sewage treatment plants (STP)	709 mg/l
Soil		22,5 mg/kg

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Use extractor hood (laboratory).

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles. Tightly sealed safety glasses. EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is



according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 8 of 18

recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. In case of prolonged or frequently repeated skin contact: Tested protective gloves are to be worn:

Suitable material:

Butyl rubber. (0,7 mm, Breakthrough time >=480 min, penetration time (maximum wearing period): 160 min): NBR (Nitrile rubber). (0,4 mm, Breakthrough time >=120 min, penetration time (maximum wearing period): 40 min)

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Protective clothing. (fire retardant.)

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Insufficient ventilation.

exceeding exposure limit values

generation/formation of aerosols

Suitable respiratory protective equipment:

gas filtering equipment (EN 141). Type : a

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

The wearing time limitations according to GefStoffV in conjunction with the rules for the use of respiratory protective devices (BGR 190) must be observed.

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour:	liquid colourless Ethanol.	
Melting point/freezing point:	Ethanoi.	not determined
Boiling point or initial boiling point and boiling range:		not determined
Flammability:		not determined
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		22 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		No information available.
Viscosity / kinematic:		not determined
Water solubility:		completely miscible
(at 20 °C)		

according to UK REACH Regulation

Hydrochl	loric Acid in Ethanol (0.1 % / 70 %)	
Revision date: 26.01.2024	Product code: 16242.xxxxx	Page 9 of 18
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density (at 20 °C):	0,86 g/cm ³	
Relative vapour density:	not determined	
Particle characteristics:	not applicable	
9.2. Other information		
Information with regard to physical hazard cla	asses	
Explosive properties		
The product is not: Explosive. In case of insu	ufficient ventilation and/or through use, explosive/highly flammable	
	onsiderable distances to a source of ignition where they can ignite,	
flash back, or explode.		
Self-ignition temperature		
Gas:	not determined	
Oxidizing properties		
none		
Other safety characteristics		
Evaporation rate:	not determined	
Solvent separation test:	not determined	
Solvent content:	not determined	
Solid content:	not determined	
Sublimation point:	not determined	
Softening point:	not determined	
Pour point:	not determined	
Viscosity / dynamic:	not determined	
Flow time:	not determined	

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Explosion risk in contact with: Oxidizing agents, strong. nitric acid. Hydrogenium peroxide. Exothermic reactions with: Alkali metals. Alkaline earth metals. Reducing agents, strong.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Keep away from heat. Protect from direct sunlight. Protect from moisture. In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting. Recommended storage temperature: < 40 °C

10.5. Incompatible materials

Strong acid. Oxidizing agents. Alkali metals. Alkaline earth metals. Peroxides. phosphorus oxides. Nitrogen oxides (NOx). Hydrogenium peroxide. Nitric acid. hydrochloric acid. Sulfuric acid. Perchlorates. Chromium oxides. Acid chlorides.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Hydrogen chloride (HCI).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation



according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 10 of 18

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
64-17-5	ethanol	ethanol						
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier			
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier			
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	ECHA Dossier			
67-63-0	2-propanol							
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier			
	dermal	LD50 mg/kg	>5000	Rabbit	ECHA Dossier			
78-93-3	butanone							
	oral	LD50 mg/kg	2054	Ratte	SDB Lieferant			
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier			
3734-33-6	Denatoniumbenzoate							
	oral	ATE mg/kg	500					
	dermal	LD50 mg/kg	>2000	Rat	suppliers SDS.			
	inhalation vapour	ATE	11 mg/l					
	inhalation dust/mist	ATE	1,5 mg/l					
7647-01-0	hydrochloric acid %							
	oral	LD50 mg/kg	2222	Rat	suppliers SDS.			

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards



according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 11 of 18

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Depending on the ingested quantity the following symptoms can be induced: a reduction of inhibitions, euphoria but also dysphoria, aggressiveness, impaired motoric skills, impaired responsiveness, blurred vision and fatigue.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
64-17-5	ethanol							
	Acute fish toxicity	LC50 mg/l	14200	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier		
	Acute algae toxicity	ErC50	275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier		
	Acute crustacea toxicity	EC50 mg/l	5012	48 h	Ceriodaphnia dubia (water flea)	ECHA Dossier		
	Crustacea toxicity	NOEC	9,6 mg/l	9 d	Daphnia magna	ECHA Dossier		
67-63-0	2-propanol							
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas	ECHA Dossier	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	1800	96 h	Scenedesmus quadricauda	ECHA Dossier		
	Acute crustacea toxicity	EC50 mg/l	>10000	48 h	Daphnia magna (24h)	ECHA Dossier	OECD Guideline 202	
78-93-3	butanone							
	Acute fish toxicity	LC50 mg/l	2993	96 h	Pimephales promelas	ECHA Dossier	OECD 203	
	Acute algae toxicity	ErC50 mg/l	1972	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	OECD 201	
	Acute crustacea toxicity	EC50	308 mg/l	48 h	Daphnia magna	ECHA Dossier	OECD 202	
3734-33-6	Denatoniumbenzoate							
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)	suppliers SDS.		
	Acute crustacea toxicity	EC50	13 mg/l		Daphnia magna (Big water flea)	suppliers SDS.		

12.2. Persistence and degradability

The product has not been tested.



according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 12 of 18

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation	•			
64-17-5	ethanol				
	other guideline	84%	20	ECHA Dossier	
	Biodegradable.				
67-63-0	2-propanol				
	EU Method C.5/ EU Method C.6	53%	5	ECHA Dossier	
	Easily biodegradable (concerning to the criteria of the OECD)			
78-93-3	butanone				
		98%	28	ECHA Dossier	
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,31
67-63-0	2-propanol	0,05
78-93-3	butanone	0,3

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

The product has not been tested.

Further information

Avoid release to the environment. Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process. Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

List of Wastes Code - used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 13 of 18

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID) 14.1. UN number or ID number: UN 1170 14.2. UN proper shipping name: ETHANOL SOLUTION 14.3. Transport hazard class(es): 3 14.4. Packing group: П Hazard label: 3 Classification code: F1 Special Provisions: 144 601 Limited quantity: 11 Excepted quantity: F2 Transport category: 2 Hazard No: 33 Tunnel restriction code: D/F Inland waterways transport (ADN) 14.1. UN number or ID number: UN 1170 14.2. UN proper shipping name: ETHANOL SOLUTION 14.3. Transport hazard class(es): 3 14.4. Packing group: П Hazard label: 3 Classification code: F1 Special Provisions: 144 601 Limited quantity: 1 L Excepted quantity: E2 Marine transport (IMDG) UN 1170 14.1. UN number or ID number: ETHANOL SOLUTION 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 3 14.4. Packing group: Ш Hazard label: 3 Special Provisions: 144 Limited quantity: 1 L



according to UK REACH Regulation

Hydr	ochloric Acid in Ethanol (0.1 % / 70 %)			
Revision date: 26.01.2024	Product code: 16242.xxxx	Page 14 of 18		
Excepted quantity: EmS:	E2 F-E, S-D			
Air transport (ICAO-TI/IATA-DGR)				
14.1. UN number or ID number:	UN 1170			
14.2. UN proper shipping name:	ETHANOL SOLUTION			
<u>14.3. Transport hazard class(es):</u> 14.4. Packing group:	3 II			
Hazard label:	3			
Special Provisions:	A3 A58 A180			
Limited quantity Passenger:	1L			
Passenger LQ:	Y341			
Excepted quantity: IATA-packing instructions - Passenger:	E2 353			
IATA-packing instructions - Passenger: IATA-max. quantity - Passenger:	555 5 L			
IATA-packing instructions - Cargo:	364			
IATA-max. quantity - Cargo:	60 L			
14.5. Environmental hazards				
ENVIRONMENTALLY HAZARDOUS:	No			
Warning: Combustible liquid. Refer to s <u>14.7. Maritime transport in bulk according to</u> not relevant <u>SECTION 15: Deculatory information</u>				
SECTION 15: Regulatory information 15.1. Safety, health and environmental regul	ations/legislation specific for the substance or mixture			
EU regulatory information				
Restrictions on use (REACH, annex XVII): Entry 3, Entry 40, Entry 75				
Directive 2010/75/EU on industrial emissions:	not determined			
Directive 2004/42/EC on VOC in paints and varnishes:	not determined			
Information according to Directive 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS			
Additional information The mixture is classified as hazardous	according to regulation (EC) No 1272/2008 [CLP].			
National regulatory information				
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juve work protection guideline' (94/33/EC).	nile		
Water hazard class (D):	1 - slightly hazardous to water			
15.2. Chemical safety assessment				
For the following substances of this mix ethanol 2-propanol butanone hydrochloric acid %	ture a chemical safety assessment has been carried out:			



according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 15 of 18

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16. Rev. 2,00, 12.02.23, Individual safety data sheet based on 10372_collect Rev. 3,0; 26.01.2024; Change of classification/labeling, Change of transport labelling



according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 16 of 18

Abbreviations and acronyms Met. Corr: Corrosive to metals Flam. Lig: Flammable liquids Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation STOT SE: Specific target organ toxicity - single exposure Aquatic Chronic: Chronic aquatic hazard ADR: Accord européen sur le transport des marchandises dangereuses par Route AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen AGW: Arbeitsplatzgrenzwert AVV: Abfallverzeichnisverordnung CAS Chemical Abstracts Service CLP: Classification, Labelling and Packaging of substances and mixtures DNEL: Derived No Effect Level d: dav(s) EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European LIst of Notified Chemical Substances ECHA: European Chemicals Agency EWC: European Waste Catalogue IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany) h: hour LOAEL: Lowest observed adverse effect level LOAFC: Lowest observed adverse effect concentration LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level NLP: No-Longer Polymers N/A: not applicable OECD: Organisation for Economic Co-operation and Development PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) REACH: Registration, Evaluation, Authorisation of Chemicals SVHC: substance of very high concern TRGS Technische Regeln fuer Gefahrstoffe UN: United Nations VOC: Volatile Organic Compounds VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe WGK: Wassergefaehrdungsklasse CLP: Classification, labelling and Packaging REACH: Registration, Evaluation and Authorization of Chemicals GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals UN: United Nations



according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 17 of 18

CAS: Chemical Abstracts Service DNEL: Derived No Effect Level DMEL: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50% EC50: Effective Concentration 50% ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration BCF: Bio-concentration factor PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Regulations concerning the international carriage of dangerous goods by rail ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) EmS: Emergency Schedules MFAG: Medical First Aid Guide MARPOL: International Convention for the Prevention of Marine Pollution from Ships IBC: Intermediate Bulk Container For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). EC/EEC: European Community/European Economic Community EU: European Union M-factor: Multiplying factor IATA: International Air Transport Association DGR: Dangerous Goods Regulations ICAO: International Civil Aviation Organization TI: Technical Instructions VOC: volatile organic compound

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure	
Flam. Liq. 2; H225	On basis of test data	
Eye Irrit. 2; H319	Calculation method	

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according to Regulation (EC) No 1272/2008 [CLP]



according to UK REACH Regulation

Hydrochloric Acid in Ethanol (0.1 % / 70 %)

Revision date: 26.01.2024

Product code: 16242.xxxxx

Page 18 of 18

- Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)