

according to UK REACH Regulation

Sudan III 0.1 %, in Glycerine Ethanol

Revision date: 23.11.2023

Product code: 15934.xxxxx

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Sudan III 0.1 %, in Glycerine Ethanol

UFI:

E41A-D6M0-FTFD-72KH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Use as laboratory reagent. Intended for scientific research and development.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	MORPHISTO GmbH	
Street:	Schumannstr. 144	
Place:	D-63069 Offenbach	
Telephone:	+49 (0) 69 / 400 3019-60	Telefax: +49 (0) 69 / 400 3019-64
E-mail:	info@morphisto.de	
Contact person:	Morphisto GmbH	
E-mail:	gefahrstoffmanagement@morphisto.	de
Internet:	http://www.morphisto.de	
1.4. Emergency telephone	Morphisto GmbH, Tel: +49(0)69 400	3019-60, Mo-Fr.: 09-16 Uhr

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 3; H226

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Pictograms:

GB CLP Regulation Signal word:



Warning

Hazard statements

H226

Flammable liquid and vapour.

Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Labelling of packages where the contents do not exceed 125 ml

Signal word:

Pictograms:





according to UK REACH Regulation

Sudan III 0.1 %, in Glycerine Ethanol

Revision date: 23.11.2023

Product code: 15934.xxxxx

Page 2 of 13

2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation	Classification (GB CLP Regulation)			
64-17-5	Ethanol			35 - < 40 %	
	200-578-6	603-002-00-5	01-2119457610-43		
	Flam. Liq. 2, Eye Irrit. 2; H225 H3				
78-93-3	butanone		< 1 %		
	201-159-0	606-002-00-3	01-2119457290-43		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE	3; H225 H319 H336 EUH066	·		
85-86-9	Sudan III			< 1 %	
	201-638-4				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc.	Limits, M-factors and ATE		
64-17-5	200-578-6	Ethanol	35 - < 40 %	
	inhalation: LC50 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg Eye Irrit. 2; H319: >= 50 - 100			
78-93-3	201-159-0	butanone	< 1 %	
	dermal: LD50 = >2000 mg/kg; oral: LD50 = 2054 mg/kg			

Further Information

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. If unconscious but breathing normally, place in recovery position and seek medical advice. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.



according to UK REACH Regulation

Sudan III 0.1 %, in Glycerine Ethanol

Revision date: 23.11.2023

Product code: 15934.xxxxx

Page 3 of 13

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect).

4.2. Most important symptoms and effects, both acute and delayed

Acute effects Mucous membrane irritation after eye contact or inhalation. Delayed effects: Impairment of inhibitory functions of the central nervous system, skin redness, nausea after ingestion of large amounts. Degreasing effect with brittle and cracked skin.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. Vapours are heavier than air and will spread at floor level. In case of fire may be liberated: Carbon monoxide (CO). Carbon dioxide (CO2).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Take precautionary measures against static discharges. Ventilate affected area. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Special danger of slipping by leaking/spilling product. Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Prevent spread over a wide area (e.g. by containment or oil barriers). Clear contaminated areas thoroughly.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8



according to UK REACH Regulation

Sudan III 0.1 %, in Glycerine Ethanol

Revision date: 23.11.2023

Product code: 15934.xxxxx

Page 4 of 13

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment (refer to section 8). Provide adequate ventilation as well as local exhaustion at critical locations. Always close containers tightly after the removal of product.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Heating causes rise in pressure with risk of bursting. Flammable vapours can accumulate in head space of closed systems. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product. Protect skin by using skin protective cream.

Further information on handling

Wash hands and face before breaks and after work and take a shower if necessary. Draw up and observe skin protection programme. Street clothing should be stored seperately from work clothing. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep only in original packaging. Protect from direct sunlight. Ensure adequate ventilation. Concentrated vapours are heavier than air.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with: food and feed. pharmaceuticals. Infectious substances. Radioactive substances. Explosive substances. Oxidizing substances. Oxidizing liquids. Organic peroxides. Self-reactive substances and mixtures. Pyrophoric solids. Substances which in contact with water form flammable gases. Ammonium nitrate and preparations containing ammonium nitrate.

Further information on storage conditions

Recommended storage temperature: 15-25 °C.

7.3. Specific end use(s)

Use as laboratory reagent. Intended for scientific research and development.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
56-81-5	Glycerol, mist	-	10		TWA (8 h)	WEL



according to UK REACH Regulation

Sudan III 0.1 %, in Glycerine Ethanol

Revision date: 23.11.2023

Product code: 15934.xxxxx

Page 5 of 13

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

DNEL/DMEL values

CAS No	Substance		_	
DNEL type		Exposure route	Effect	Value
56-81-5	Glycerol			
Worker DNEL,	long-term	inhalation	local	56 mg/m³
64-17-5	Ethanol			•
Worker DNEL,	acute	inhalation	local	1900 mg/m³
Worker DNEL,	long-term	dermal	systemic	343 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	950 mg/m³
Consumer DN	EL, acute	inhalation	local	950 mg/m³
Consumer DN	EL, long-term	dermal	systemic	206 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	114 mg/m³
Consumer DN	EL, long-term	oral	systemic	87 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmen	tal compartment	Value
64-17-5	Ethanol	
Freshwater		0,96 mg/l
Freshwater	(intermittent releases)	2,75 mg/l
Marine water		0,79 mg/l
Marine water (intermittent releases)		2,75 mg/l
Freshwater	sediment	3,6 mg/kg
Marine sedi	nent	2,9 mg/kg
Secondary p	oisoning	0,72 mg/kg
Micro-organ	isms in sewage treatment plants (STP)	580 mg/l
Soil		0,63 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment. Provide adequate ventilation. Provide adequate ventilation as well as local exhaustion at critical locations. Provide washing facilities at the workplace, provide an eye shower or eyewash bottle and mark them. Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. Safety glasses according to EN 166.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four



Sudan III 0.1 %, in Glycerine Ethanol

Revision date: 23.11.2023

Product code: 15934.xxxx

Page 6 of 13

control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

In case of prolonged or frequently repeated skin contact: Tested protective gloves are to be worn: Suitable material:

Butyl rubber. 0,7mm: Breakthrough time (maximum wearing time): >480 min. penetration time (maximum wearing period): 160 min.

NBR (Nitrile rubber). 0,4mm. Breakthrough time>=120min. penetration time (maximum wearing period):40min.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Before using check leak tightness / impermeability.

Skin protection

Use of protective clothing. Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Suitable respiratory protective equipment: gas filtering equipment (EN 141). Type: A

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

s. i. information on pasic physical and che	mear properties	
Physical state:	Liquid	
Colour:	red	
Odour:	ethanolic	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and		78 °C
boiling range:		
Flammability:		not determined
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		26 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:		easily soluble
(at 20 °C)		
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		58 hPa
(at 20 °C)		
Density (at 20 °C):		1,03 g/cm ³
Relative vapour density:		not determined
Particle characteristics:		not applicable
9.2. Other information		

Information with regard to physical hazard classes



Sudan III 0.1 %, in Glycerine Ethanol

Revision date: 23.11.2023

Product code: 15934.xxxxx

Page 7 of 13

Explosive properties The product is not: Explosive. Oxidizing properties The product is not: oxidising.

Other safety characteristics Evaporation rate:

Solid content:

not determined not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Explosion risk in contact with: Oxidizing agents. Nitric acid. peroxides, for example hydrogen peroxide Exothermic reactions with: Alkali metals. Alkaline earth metals. Reducing agents, strong.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. UV-radiation/sunlight.

10.5. Incompatible materials

Materials to avoid: Substances which in contact with water, emit flammable gases. Organic peroxides Oxidizing substances. Alkali metals. Acid chlorides. Oxidizing agents. Rubber. various plastics.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
64-17-5	Ethanol	Ethanol						
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier			
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier			
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	ECHA Dossier			
78-93-3	butanone							
	oral	LD50 mg/kg	2054	Ratte	SDB Lieferant			
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier			

Irritation and corrosivity

Based on available data, the classification criteria are not met.



Sudan III 0.1 %, in Glycerine Ethanol

Revision date: 23.11.2023

Product code: 15934.xxxx

Page 8 of 13

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
64-17-5	Ethanol						
	Acute fish toxicity	LC50 mg/l	14200		Pimephales promelas (fathead minnow)	ECHA Dossier	
	Acute algae toxicity	ErC50	275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier	
	Acute crustacea toxicity	EC50 mg/l	5012	48 h	Ceriodaphnia dubia (water flea)	ECHA Dossier	
	Crustacea toxicity	NOEC	9,6 mg/l	9 d	Daphnia magna	ECHA Dossier	
78-93-3	butanone						
	Acute fish toxicity	LC50 mg/l	2993	96 h	Pimephales promelas	ECHA Dossier	OECD 203
	Acute algae toxicity	ErC50 mg/l	1972		Pseudokirchnerella subcapitata	ECHA Dossier	OECD 201
	Acute crustacea toxicity	EC50	308 mg/l	48 h	Daphnia magna	ECHA Dossier	OECD 202

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name						
	Method	Value	d	Source			
	Evaluation						
64-17-5	Ethanol						
	other guideline	84%	20	ECHA Dossier			
	Biodegradable.						
78-93-3	butanone						
		98%	28	ECHA Dossier			
	Readily biodegradable (according to OECD criteria).						

12.3. Bioaccumulative potential

The product has not been tested.



according to UK REACH Regulation

Sudan III 0.1 %, in Glycerine Ethanol

Revision date: 23.11.2023

Product code: 15934.xxxx

Page 9 of 13

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	Ethanol	-0,31
78-93-3	butanone	0,3
85-86-9	Sudan III	7,63

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself. Contaminated packages must be completely emptied and can be re-used following proper cleaning.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1170
14.2. UN proper shipping name:	ETHANOL SOLUTION
14.3. Transport hazard class(es):	3
14.4. Packing group:	111
Hazard label:	3
	3
Classification code:	F1
Special Provisions:	144 601
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E
Inland waterways transport (ADN) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u>	UN 1170 ETHANOL, SOLUTION 3



٦

Safety Data Sheet

according to UK REACH Regulation

Revision date: 23.11.2023	Sudan III 0.1 %, in Glycerine Ethanol Product code: 15934.xxxxx	Page 10 of 1
14.4. Packing group:	III	
Hazard label:	3	
	3	
Classification code:	F1	
Special Provisions:	144 601	
Limited quantity:	5 L	
Excepted quantity:	E1	
Marine transport (IMDG)		
14.1. UN number or ID number:	UN 1170	
14.2. UN proper shipping name:	ETHANOL SOLUTION	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	 -	
Hazard label:	3	
Special Provisions:	144 223	
Limited quantity:	5 L	
Excepted quantity:	E1	
EmS:	F-E, S-D	
Air transport (ICAO-TI/IATA-DGR)		
14.1. UN number or ID number:	UN 1170	
14.2. UN proper shipping name:	ETHANOL SOLUTION	
14.3. Transport hazard class(es):	3	
<u>14.4. Packing group:</u> Hazard label:	III 3	
Special Provisions:	A3 A58 A180	
Limited quantity Passenger:	10 L	
Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:	355	
IATA-max. quantity - Passenger: IATA-packing instructions - Cargo:	60 L 366	
IATA-max. quantity - Cargo:	220 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
14.6. Special precautions for user		
Warning: Combustible liquid.		
14.7. Maritime transport in bulk according not applicable	to IMO instruments	
SECTION 15: Regulatory information		

EU regulatory information



Sudan III 0.1 %, in Glycerine Ethanol			
Revision date: 23.11.2023	Product code: 15934.xxxxx	Page 11 of 13	
Restrictions on use (REACH, annex XVII Entry 3, Entry 40, Entry 75 Information according to 2012/18/EU (SEVESO III):): P5c FLAMMABLE LIQUIDS		
National regulatory information			
Employment restrictions:	Observe restrictions to employment for juveniles according to the work protection guideline' (94/33/EC).	'juvenile	
Water hazard class (D):	1 - slightly hazardous to water		
15.2. Chemical safety assessment			
For the following substances of this mixture a chemical safety assessment has been carried out: Ethanol butanone			
SECTION 16: Other information			
Changes			

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16. Rev.: 1,00; 15.12.2020; Initial release Rev. 2,0; 23.11.2023; general adjustment(s), Change of classification/labeling, New UFI code was generated.



according to UK REACH Regulation

Sudan III 0.1 %, in Glycerine Ethanol

Revision date: 23.11.2023

Product code: 15934.xxxxx

Page 12 of 13

_	
	Abbreviations and acronyms
	CLP: Classification, labelling and Packaging
	REACH: Registration, Evaluation and Authorization of Chemicals
	GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
	UN: United Nations
	CAS: Chemical Abstracts Service
	DNEL: Derived No Effect Level
	DMEL: Derived Minimal Effect Level
	PNEC: Predicted No Effect Concentration
	ATE: Acute toxicity estimate
	LC50: Lethal concentration, 50%
	LD50: Lethal dose, 50%
	LL50: Lethal loading, 50%
	EL50: Effect loading, 50%
	EC50: Effective Concentration 50%
	ErC50: Effective Concentration 50%, growth rate
	NOEC: No Observed Effect Concentration
	BCF: Bio-concentration factor
	PBT: persistent, bioaccumulative, toxic
	vPvB: very persistent, very bioaccumulative
	ADR: Accord européen sur le transport des marchandises dangereuses par Route
	(European Agreement concerning the International Carriage of Dangerous Goods by Road)
	RID: Regulations concerning the international carriage of dangerous goods by rail
	ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
	(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
	intérieures)
	IMDG: International Maritime Code for Dangerous Goods
	EmS: Emergency Schedules
	MFAG: Medical First Aid Guide
	IATA: International Air Transport Association
	ICAO: International Civil Aviation Organization
	MARPOL: International Convention for the Prevention of Marine Pollution from Ships
	IBC: Intermediate Bulk Container
	VOC: Volatile Organic Compounds
	SVHC: Substance of Very High Concern
	For abbreviations and acronyms, see table at http://abbrev.esdscom.eu
	For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
	assessment, chapter R.20 (Table of terms and abbreviations).
	Flam. Liq: Flammable liquids
	Eye Irrit: Eye irritation
	STOT SE: Specific target organ toxicity - single exposure
	Classification for mixtures and used evaluation method according to GB CLP Regulation
	Classification Classification procedure

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according EC regulation 1272/2008 (CLP):



according to UK REACH Regulation

Sudan III 0.1 %, in Glycerine Ethanol

Revision date: 23.11.2023

Product code: 15934.xxxxx

Page 13 of 13

Self-classification (mixture, test data).

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)